

LCD PROJECTOR

UltraPortable

CP-X380W

2000 ANSI Lumens

- Native XGA Resolution
- Contrast Ratio (400:1)
- 7 lbs.
- 2 RGB Inputs
- RGB Output
- Component / Composite / S-video Inputs
- HDTV Theater Ready
- FCC class B
- 34 dB (Whisper Mode)
- Manual Zoom / Manual Focus
- Digital Keystone Correction
- Wireless Remote Controller with Laser Pointer



Forget-me-not Features:

- Δ 16:9 mode
- Δ Reverse image function for ceiling mount
- Δ Color temperature and gamma correction
- Δ Digital zoom and freeze function
- Δ Kensington slot

Input Terminal



HITACHI
Inspire the Next

CP-X380W Ultra-Portable LCD Projector

Model	CP-X380W
--------------	-----------------

Performance Specifications

Liquid crystal panel structure	0.9" polysilicon active-matrix TFT x 3
Number of Pixels	786,432 pixels (H1024 x V768)
Resolution	1024 x 768 color pixels
Lens	Manual zoom 1:1.3 (F1.74 - 2.08)
Lamp power consumption	200W UHB
Average lamp life	2,000 hours
Brightness	2,000 ANSI lumens (1,600 ANSI lumens in Whisper Mode)
Contrast ratio	400 : 1
Speakers	1W X 2 Stereo
Power supply	AC100-120V / AC220-240V 50 / 60HZ
Power consumption	310W
Operating temperature	0° - 35° C (32° - 95° F)
Input signals	VGA, SVGA, XGA, SXGA (COMPRESSED), MAC13", MAC16", NTSC, NTSC4.43, PAL, SECAM PAL-M, PAL-N, PAL60,
Component video	480i, 575i, 480p, 1080i, 720p
Noise level	40 dB (34 dB in Whisper Mode)

Interface Connectors

RGB input	ANALOG RGB	15-Pin D-sub shrink x 2
	AUDIO	Mini-jack x 2
Video input	S-VIDEO	Mini-jack x 1
	COMPOSITE	RCA jack x 1
	COMPONENT	RCA jack x 3
	AUDIO	RCA jack x 2
Audio output	ANALOG RGB	3.5 Stereo mini jack
Control terminals		15 Pin D-sub shrink x 1, RS-232C (serial)
USB		Remote control mouse

Chassis


Dimensions	11.7" x 3.0" x 8.98" (W x H x D)
Weight	7 lbs.

Supplied Accessories

Wireless remote control with Laser Pointer (AA batteries), PS / 2 mouse cable, Batteries, Power cord (U.S., UK, Euro), RCA Component cable, RGB cable, Multiple language operator / safety manual, Handle strip and Carry case

Screen Size (inches) <i>Diagonal</i>	Min. (a)	Max. (a)
40	62	86
60	94	128
80	127	164
100	160	205
120	192	246
150	241	308
200	323	411

a: Distance from the LCD projector to the screen
The projection distance shown in the table below are for full size



HITACHI

**Hitachi America, Ltd.
Computer Division**
2000 Sierra Point Parkway, MS:760
Brisbane, CA 94005-1835
Tel (800) 225-1741
Fax (650) 244-7776
Web Site: <http://www.hitachi.com/mmp>
For information on other Hitachi products:
1-800-HITACHI (800-448-2244)

Hitachi Canada, Ltd.
6740 Campobello Road
Mississauga, Ontario L5N 2L8
Tel (905) 821-4545
(800) 906-4482
Fax (905) 814-0848
Web Site: <http://www.hitachi.ca>

Specifications and product offerings are subject to change without notice ©2002 Hitachi America, Ltd. All rights reserved. Printed in US CP-X380W DS.01.02