



## PLC-XC10/ SC10



### Compact Portable LCD Projectors

- ◆ XGA (XC10) & SVGA (SC10) resolution
- ◆ 3000 ANSI lumens
- ◆ Optional Multi-card Imager Box –  
Wired/ Wireless LAN/ Flash Card Viewer
- ◆ 2 Data, 1 Video Input
- ◆ Auto Keystone Correction
- ◆ Auto Focus
- ◆ USB Security Function
- ◆ Weighs only 5.8Kg

|                        |  |
|------------------------|--|
| Model name             | PLC-XC10/ SC10   |
| Panel                  | 0.99 inch TFT p-Si x 3   |
| No. of pixels          | 1024 x 768 (XC10), 800 x 600 (SC10)  |
| Projection lamp        | 300W NSH Lamp  |
| Brightness (typical)   | 3000 ANSI lumens   |
| Uniformity             | 90% (corner to centre)   |
| Contrast ratio         | 350:1  |
| Up-Down ratio          | 9:1, Digital Keystone $\pm 40^\circ$ vertical, $\pm 20^\circ$ horizontal   |
| Projection lens        | F 1.7 - 2.1, f=33.6 – 43.2mm   |
| Throw ratio            | 1.65 – 2.20:1  |
| Screen size            | 31"-300"   |
| AV Signal              | Input: Composite (RCA), Component (RCAX3),<br>S-Video (mini DIN 4 pin), Stereo (RCAX2)   |
| Color systems          | PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N  |
| PC Signal              | Input: DVI-I x 1 (Digital/Analogue)<br>Audio input: Stereo x 1 (mini jack)<br>Audio output: Stereo x 1 (mini jack)<br>Output: RGB (D-Sub15), switchable 2 <sup>nd</sup> data input |
| Control Port           | Serial x 1 (Mini DIN8-pin), USB type B x 1, USB type A Port  |
| Computer compatibility | SXGA/XGA/SVGA/VGA/MAC  |
| Scanning frequency     | H sync 15~100kHz, V Sync 50~100Hz Dot clock 140 MHz  |
| Sound output           | 1.0W   |
| Voltage                | 100V-240V AC (auto voltage)  |
| Dimensions(W x H x D)  | 390 x 112 x 274 mm   |
| Weight                 | 5.8kg  |