

# Galaxy NW-12

WUXGA, 12,000 lumens, three-chip DLP 3D stereo projector



Barco's Galaxy NW-12 is the world's first WUXGA (1920x1200) projector with built-in 3D stereo capabilities. It is an ideal solution for environments that require versatile visualization that allows them to view and analyze multiple sources simultaneously - in any combination of 2D and 3D stereo. The Galaxy NW-12 is a perfect companion for cross-team collaboration rooms in the oil and gas industry, automotive design review centers, engineering hubs or immersive research centers in higher education.

### Multiple channels, one seamless image

The Galaxy NW-12 comes equipped with unique, Barco-engineered technology for multi-channel set-ups:

- **Electronic or optical edge blending** creates one continuous image across the entire screen, without blurry overlap zones, thanks to new alpha and beta planes
- **Linked constant light output (CLO)** and equalize brightness levels across the entire display system
- **Linked DynaColor** technology ensures perfect color matching between channels
- **Bi-cubical warping** (geometry correction) ensures that an image is projected correctly, with an extremely high level of accuracy, across curved, non-flat surfaces

### Compatibility with XDS Control Center software suite

Barco's Galaxy NW-12 can be integrated with Barco's multi-windowing XDS Control Center software suite. It supports single, two- as well as multi-channel setups, and results in the following key benefits:

- **Familiar Windows desktop interface:** no need to learn new interfaces.
- **Source multi-windowing:** all relevant data on one screen, in any configuration
- **Large-screen videoconferencing:** collaboration and data-sharing in real-time
- **Centralized maintenance and security:** remote control and security overviews

BARCO

Visibly yours

# Galaxy NW-12 technical specifications

<b>Display capabilities</b>	<b>Light output</b>	12,000 lumens
	<b>Contrast</b>	up to 2,000:1
	<b>Resolution</b>	WUXGA (1920x1200)
	<b>Chip technology</b>	Three-chip DLP
<b>Lamps</b>	<b>Lamp</b>	2 kW Xenon
	<b>Lamp warranty</b>	750 hrs warranted, max. 1000 hrs
<b>Dimensions</b>	<b>Weight</b>	70 kg (154.2 lbs) net - 85 kg (187.4 lbs) shipping weight
	<b>Height - width - length</b>	345 / 590 / 913 mm 13.58" / 23.22" / 35.94"
	<b>Available zoom lenses</b>	
<b>Lenses</b>	TLD+ (1.5-2.0:1)	R9862010
	TLD+ (2.0-2.8:1)	R9862020
	TLD+ (2.8-4.5:1)	R9862030
	TLD (4.5-7.5:1)	R9862040
	<b>Available fixed focal lenses</b>	
	TLD+ (0.73:1)	R9862000
	TLD+ (1.2:1)	R9840775
	<b>Lens shift range</b>	
	Horizontal shift up to +/- 55%	
	Vertical shift up to +/- 110%	
<b>Features</b>	<b>Special features</b>	
		Multiple stereo capabilities (Active, Active Infitec, Polarized)
		Source and PiP operation through Windows OS
		Standard full geometry correction
		Sealed, liquid-cooled engine
		Multi-channel features

<b>Inputs and outputs</b>	<b>Standard inputs</b>	
		1x 5-BNC (RGBHV, RGBS or RGBsB)
		1x Composite video (BNC)
		1x S-Video (4-pin mini DIN)
		1x DVI (HDCP compliant)
		1x VGA (D15)
	3 stereo sync inputs (mini-DIN)	
	<b>Optional inputs (1 free layer)</b>	
	SDI/HD-SDI input	
	<b>Communication ports</b>	
	RS232 (on D9)	
	10/100 Mb/s Ethernet (on RJ45)	
<b>Compatibility</b>	<b>Video</b>	
		PAL, SECAM, NTSC video signals in Composite, S-video, component or RGB format
		All current HDTV standards (720i, 720p, 1080i, 1080p) in Component or RGB format
	<b>Data</b>	
		All computer graphics formats up to QXGA @ 120 Hz
	Analog sources with a pixel clock of up to 270 MHz	
	DVI sources with a pixel clock of up to 165 MHz	
<b>Safety</b>	<b>Safety standards</b>	
		ETL60950 and EN60950
		CE compliant
	CCC compliant	
<b>Power</b>	<b>AC power</b>	
		200 - 240 VAC/50-60 Hz
	<b>Max. power consumption / dissipation</b>	
	2,800 Watt / 9,560 BTU	
<b>Order info</b>	Galaxy NW-12	R9040410
	New 2kW lamp	R9843080
	Refurbished lamp	R9843090
	QXGA RGBHV input	R9843020
	DVI/D15 input (HDCP)	R9843045
	SDI/HD-SDI	R9843040



R5990138 September 2008

DLP technology by Texas Instruments offers crystal clear images with superior quality. DLP is a trademark of Texas Instruments.

The information and data given are typical for the equipment described. However any individual item is subject to change without any notice.

Barco  
Aviation & Simulation Division

contact.bps@barco.com

Noordlaan 5  
8520 Kuurne - Belgium  
Tel. +32 56 36 82 11  
Fax +32 56 36 85 26



Visibly yours