

NEC LT157

Article Number:	50021523
Display:	3 x 2.3 cm p-Si/MLA* LCD Panel
Lamp:	130 W DC NSH (110 W with ECO mode)
Lamp Life:	1500 hours (2500 hours with ECO mode)
Brightness (ANSI Lumen):	1500 (1200 with ECO mode)
Contrast Ratio:	600:1
Lens:	F 1.7-2.1, f= 36.5-43.7 mm
Minimum Image Diagonal:	63 cm
Maximum Image Diagonal:	762 cm
Throwing Distance:	1.17 m – 14.7 m
Projection Factor:	1.91–2.41 : 1
Colour Reproduction:	16.77 Mio.
Frequency:	Horizontal: 15-100 kHz, vertical: 50–120 Hz
Native Resolution:	1024 x 768 (XGA) with 60 Hz
Supported Resolutions:	1600 x 1200 (UXGA), 1280 x 1024 (SXGA), 1152 x 900 (SGI, SUN), 1152 x 870 (Mac), 1920 x 1080 (HDTV 1080i), 1280 x 720 (HDTV 720p) with Advanced AccuBlend™ Technology, 800 x 600 (SVGA), 832 x 624 (Mac), 640 x 480 (VGA/Mac), 768 x 576 (PAL 15,6 kHz), 640 x 480 (NTSC 15,7 kHz), 720 x 483 (SDTV 480p)
IN / OUTPUT TERMINAL	
RGB	1 Input: Mini D-sub 15-pin; component signal (YPbPr) by RGB
VIDEO	1 Input: Cinch
S-VIDEO	1 Input: DIN 4-pin
RGB/VIDEO/S-VIDEO AUDIO	1 Input: 3.5 mm Stereo mini jack
PC Control (RS-232)	1 Input: DIN 8-pin
USB	1 Input: A-Type
PC-Card Slot	1 Input: Compact Flash Type-1
Video Signals:	PAL/PAL 60/NTSC/SECAM/NTSC 4.43
Audio Functions:	0.5 W mono speaker
Zoom Adjustment:	Manual
Focus Adjustment:	Manual
Benefits:	Digital zoom up to 400%, Pulldown menu, Keystone correction up to ±30° (digital), PC-Card Slot, remote control with laserpointer and mouse control, help function, Plug&Play, Colour and Gamma correction, Chalk Board
Remote Control:	Source select, auto picture adjustment, magnify, freeze, laserpointer, mouse control, help function, aspect ratio
Dimensions (W x H x D):	207 x 63 x 266 mm (without lense and feet)
Weight:	2.2 kg
Power Supply:	100-120/200-240 V AC ± 10%, 50/60 Hz
Power Consumption:	200 W max. (175 W with ECO mode)
Fan Noise:	Normal: < 42 dB (A) (fan/max), with ECO mode: < 37 dB (A) (fan/min)
Safety/Ergonomics:	CE, TÜV GS
Warranty:	Projector: 3 years pan-European on-site service Lamp: 2500 hours (ECO mode) or max. 6 months
Shipping Contents:	Projector, remote control with laserpointer and mouse control, IR-Receiver, Mini D-Sub signalcable, power cord, lens cap, softcase, users manual, CD-Rom
Optional Accessories:	Hardcase, lamp, YUV cable
Available from:	April 2002

* New Short arc High pressure

All specifications are subject to change without notice. Status March 2002

- **Native Resolution 1024 x 768 (XGA)**
- **Max. Resolution 1600 x 1200 (SXGA) with Advanced AccuBlend™ Technology**
- **Brightness 1500 ANSI Lumen**
- **Lightweight 2.2 kg**
- **Digital Zoom up to 400 %**
- **16:9 aspect ratio**
- **Keystone correction up to ±30° (digital)**
- **Auto source select**
- **Silent fans (only 37 dB (A)/ECO mode)**
- **2500 hours lamp life time (ECO mode)**
- **PC-Card-Viewer**
- **Chalk Board**
- **3 years warranty including on site service (repair/exchange)**



Peripherals
Plasma Monitors

NEC Deutschland GmbH
Reichenbachstr. 1
85737 Ismaning
Germany

Phone:
+49-89-9 6274-0

Web site:
www.necd.de

Empowered by Innovation

NEC