



MultiSync® MT1035™

The new MultiSync MT1035 projector has all the features professionals demand for excellent image quality, precise control and exceptional ease of use.



- Advanced AccuBlend™ intelligent pixel blending technology displays high-resolution images with remarkably true resolution and now enables digital keystone correction.
- New lamp technology delivers higher brightness and whiter whites with lower power consumption.
- Dust resistant LCD panels provide a better image over time.
- Full-featured remote control enables quick, one-button access to key features and

- includes a built-in mouse, laser-pointer and 360 degree infrared system.
- On-screen controls let you make image adjustments including brightness, color, contrast, sharpness, position and keystone correction. New color control lets you adjust red, green and blue individually.
- Improved auto feature automatically centers the image on the screen.
- Optional PC card viewer lets you store and transport commonly used slides or images on a PCMCIA card.

- Sturdy construction features an integrated carrying handle plus compatibility with the Kensington security lock system.
- Included introductory video and Quick Connect Guide provides hands-on demonstration of key features and projector set-up.
- Exclusive InstaCareSM service guarantees a replacement projector within 24 hours, or repair and return of the original unit within 72 hours.

MultiSync® MT1035 Specifications Model #LCDMT1035

LCD Panel:	1.3" x 3, 1024 x 768 p-Si TFT active matrix
Lens:	Power Zoom, Power Focus, F 2.0 f=48-79mm
Lamp:	150 Watt NSH user replaceable, long life lamp
Image Size:	Min 25" (63.5cm) Max 320" (812.8cm)
Projection Distance:	Min 2.5 ft (.76m) Max 47.2 ft (14.4m)
Light Output:	1300 ANSI Lumens
Contrast Ratio:	300:1
Color Reproduction:	16,777,216 colors simultaneously
Synchronization Range:	Horizontal: 15 kHz to 85 kHz (non-interlaced) Vertical: 50 Hz to 85 Hz
RGB Input Signals:	Visual: 75 ohm 0.7 Vp-p positive, Sync TTL Audio: 47k ohm 0.4V rms
Input Terminals:	Visual: 2x 15pin Mini D-Sub Audio: Stereo Mini Jack
Output Terminals:	Visual: RGB Throughout Audio: Stereo Mini Jack
PC Compatibility:	640x480: 60, 72, 75 and 85Hz vertical refresh 800x600: 56 to 75 and 85Hz vertical refresh 1024x768: 60, 70, 72, 75 and 85Hz vertical refresh 1280x1024: Advanced AccuBlend
Macintosh Compatibility:	640x480: 60 and 67Hz vertical refresh 832x624: 75Hz vertical refresh
Video Input Signals:	Visual: S-Video Y: 75 ohm 1.0Vp-p, S: 75 ohm 0.28Vp-p Audio: 47k ohm 0.4V rms
Input Terminals:	Visual: RCA Audio: RCA x 2
Horizontal Resolution:	NTSC 550 lines PAL/SECAM/NTSC 4.43 350 lines
Video Compatibility:	NTSC/PAL/SECAM/NTSC 4.43

Audio:	Built-in stereo speakers (2 x 2w) with Audio out capability
Remote Control Functions:	Computer Mouse Control with left and right click buttons, Built-in Laser Pointer, Source Selection, Volume, Zoom, Focus, Picture Magnification, Position, Picture Freeze, Picture Mute, Keystone
On-screen Controls Source Selection Menu: Image Adjust Menu:	Video, S-Video, RGB 1, RGB 2, PC Card Volume, Brightness, Contrast, Color, Tint, Sharpness, Image Mode, H Position, V Position, Auto Picture, Picture Adjust, Fine Picture Adjust, Keystone, White Balance
Power Menu:	Lamp Timer, Auto Start, Power Management, Keystone Save, On-screen Mute
Settings Menu:	Image Capture, Background, Video Standard, Set Position, Language Select, Pointer, Reset
Fan Noise:	Less than 42dB
Power Requirement:	100-120v/220-240v AC, 50Hz/60Hz
Power Consumption:	250 Watts
Dimensions: W x H x D	11.4 x 5.7 x 14.9 inches (29.0 x 14.5 x 37.8cm)
Net Weight:	16.8 lbs.
Supplied Accessories:	Wired/Wireless Remote Control with wireless mouse and laser pointer, Mouse Cables, Signal Cable, Mac Cable Adapter, Power Cable, Remote Cable, Introductory Video, Quick Connect Guide, Users Manual, Registration Card
Safety and Regulation:	FCC: Class "A" UL: 1950 C-UL
Environmental:	Temperature: 32-104°F (0-40°C), operational Humidity: 20% to 80%, operational
Warranty:	MT: 2-year limited, parts and labor including InstaCare 24-hour replacement service Lamp: 2000 hours or 6 months, whichever comes first

For the location of the MultiSync MT dealer nearest you or for more information on MultiSync MT accessories, call 1-800-NEC-INFO.

To speak to a MultiSync MT customer service representative, call 1-800-836-0655.

For more information via fax, call NEC FastFacts at 1-800-366-0476 and request Catalog #1.

MultiSync is a registered trademark, InstaCare is a service mark and MT1035, AccuBlend, FastFacts, OSM and the NEC Technologies icon are trademarks of NEC Technologies, Inc. All other brand or product names are trademarks or registered trademarks of their respective holders. All specifications subject to change without notice.