

Wireless Ultra Portable LCD projectors



PLC-XL20

- ◆ XGA resolution
- ◆ 1500 ANSI lumens
- ◆ Optional multi-card imager box – Wired/ Wireless/ Flash Card Viewer
- ◆ Monitor output – Switchable 2nd data input
- ◆ Electronic keystone correction
- ◆ Manual zoom and focus
- ◆ Durable compact design
- ◆ Remote control with laser pointer
- ◆ Short-throw flex lens 1.25-1.95:1
- ◆ Weighs only 2.9kg

Model name	PLC-XL20
Panel	0.79 inch TFT p-Si x 3
No. of pixels	1024 x 768
Projection lamp	200W UHP Lamp
Brightness (typical)	1500 ANSI lumens
Uniformity	85% (corner to centre)
Contrast ratio	450:1
Up-Down ratio	9:1, Digital Keystone $\pm 40^\circ$ vertical, $\pm 20^\circ$ horizontal
Projection lens	F 1.7 - 2.5, f=20 – 30mm
Throw ratio	1.25 – 1.95:1
Screen size	40"-300"
AV Signal	Input: Composite (RCA), Component (D-Sub15), S-Video(DIN4) Stereo (RCAx2)
Color systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
PC Signal	Input: DVI-I x 1 (Digital/Analogue), RGB (D-Sub15) Audio input: Stereo x 1 (mini jack) Audio output: Stereo x 1 (mini jack) Output: RGB (D-Sub15), switchable to 2 nd Data Input
Control Port	Serial x 1 (Mini DIN8-pin), USB type B x 1
Computer compatibility	SXGA/XGA/SVGA/VGA/MAC
Scanning frequency	H sync ~100kHz, V Sync ~100Hz Dot clock 140 MHz
Sound output	1.0W mono
Voltage	100V-240V AC (auto voltage)
Dimensions(W x H x D)	298 x 71 x 218 mm
Weight	2.9kg