

2200 ANSI Lumens

SVGA Resolution

Auto Brightness Function



Boxlight Beacon

Technical Specifications

Brightness: 2200 ANSI lumens

Lamp: 180 watt, NSH

Lamp life: 2000 hours

Colors: 16.7 million

Aspect Ratio: 4:3, 16:9 compatible

Contrast Ratio: 500:1

Resolution: 800 x 600 true SVGA and compressed 1280 X 1024 SXGA

Projection Lens: manual zoom

1:1.2 zoom ratio, F/1.75-2.1, f=26.7-32mm

Throw Distance: 4.75-37.4ft, 1.45-11.29m

Inputs: 2-15 pin Computer, 1-composite, 1-S-Video, 1-mini-jack audio

Outputs: 1-RGB Computer out, 1-USB mouse, 1-RS-232

Horiz. scan frequency: 15-100KHz

Vertical refresh rate: 43-120 Hz

Diagonal Image Size: 40-300in

Keystone: +/- 30 degrees vertical

Display Type: 3-0.7in TFT polysilicon LCDs

Video: NTSC, PAL, SECAM, 1080i, 720p, 480p

Adjustments: on-board and a remote

Dimensions (WxHxD):

12.2in x 3.8in x 10.6in

310mm x 96mm x 270mm

Weight: 6 lb / 2.7 kg

Power Supply: 100-240V, 50/60Hz auto change

Warranty: two-year parts and labor (120-day/500 hour lamp guarantee)

Compatibility: SXGA, XGA, SVGA, VGA, Mac

Decibel rating: 33 dB / 30 dB eco

Power Consumption: 250 Watts

Soft Power On/Off: Yes

FCC certification: Class B



19472 Powder Hill Place Ste 100
Poulsbo, WA 98370

To Contact BOXLIGHT

Direct 800.762.5757

Education 800.689.6676

Government 800.497.4009

International 360.779.7901

Internet www.boxlight.com