

NEC VT58

Article No.:	50029520
Display:	3 x 1.52 cm (0.6") p-Si mit MLA LCD-Panel
Lamp:	150 W DC (120 W Eco Mode)
Lamp Life:	4,000 hrs*
Brightness:	1,600 ANSI Lumens
Contrast Ratio:	600:1
Lens:	F= 1.7–2.07, f= 18.9–22.7 mm
Minimum Image Diagonal:	53 cm
Maximum Image Diagonal:	762 cm
Throwing Distance:	0.7–11 m
Projection Factor:	1.5–1.8:1
Frequency:	Horizontal: 15–100 kHz (RGB: 24 kHz–100 kHz), vertical: 50–120 Hz
Native Resolution:	1,024 x 768 (XGA)
Supported Resolutions:	1,600 x 1,200 (UXGA), 1,920 x 1,080 (HDTV 1,080i/60, HDTV 1,080i/50), 1,280 x 720 (HDTV 720p), 1,280 x 1,024 (SXGA), 1,280 x 1,024 (Mac23"), 1,152 x 870 (Mac21"), 1,024 x 768 (XGA) with Advanced AccuBlend™ Technology, 800 x 600 (SVGA), 832 x 624 (Mac16"), 640 x 480 (VGA/Mac13"), 720 x 480 (SDTV 480p), 720 x 480 (DVD progressive), 720 x 576 (DVD progressive)
Input/Output Terminal:	
RGB Analog	1 Input: Mini D-SUB, 15-pin, shared with component (YPbPr) and SCART-RGB 1 Output: Mini D-SUB, 15-pin
Video	1 Input: phono jack
S-Video	1 Input: DIN 4-pin (Hoseiden Connection)
Audio	1 Input: 3.5 mm stereo mini jack (computer 1 and 2) 1 Input: phono jack stereo (Video and S-Video)
PC Control (RS-232)	1 Input: D-SUB, 8-pin (female)
Video Compatibility:	PAL/PAL60/NTSC/SECAM/NTSC 4.43/PAL-N/PAL-M
Audio Functions:	1 x 1 W mono speaker
Zoom Adjustment:	Manual
Focus Adjustment:	Manual
Benefits:	manual vertical Keystone Correction (V= ±30°), manual wall color correction, color management system, RS-232 control, Quick-Start/Quick Power-Off-, sleep timer-, help-, security function, Plug&Play, OSD with 21 languages, short throw lens, source select with beep function
Remote Control (RD-427E):	Source select, picture adjust, picture mute, page control, auto adjust, freeze function, digital zoom, volume, aspect ratio, lamp mode
Dimensions (W x H x D):	309 x 112 x 258 mm (without lens and feet)
Weight:	2.8 kg
Power Supply:	100–120/200–240 V AC/50–60 Hz
Power Consumption:	215 W max./standby mode 7.4 W
Fan Noise:	25 dB (A)*
Safety/Ergonomics:	CE, TUV GS
Warranty:	Projector: 3 years pan-European premium service Lamp: 6 months, max. 1,000 hrs**
Shipping Contents:	Projector, IR remote control, Mini D-SUB signal cable, 4.5 m power cord, lens cap, CD-ROM, handle, soft carrying case
Optional Accessories:	Lamp (VT80LP), ceiling mount kit (VT80CM)
Available from:	November 2005

*Eco Mode **please refer to our warranty conditions under: www.de.nec.de

All specifications are subject to change without notice. Status: October 2005

- Native resolution: 1,024 x 768 (XGA)
- Maximum resolution: 1,600 x 1,200 (UXGA) compressed format
- Brightness: 1,600 ANSI Lumens
- Whisper quiet: 25 dB (A)*
- Quick-Start/Quick Power-Off function
- manual vertical Keystone Correction
- Wall color correction (manual)
- Sleep timer function
- Short throw lens
- 4,000 hrs* lamp life
- 3 years warranty**



Peripherals

Projectors

NEC Deutschland GmbH
Reichenbachstr. 1
85737 Ismaning
Germany

Phone:
+49(0)89-9 62 74-0

Web site:
www.de.nec.de