


# P1203 PROJECTOR

## DLP Technology – 3D Ready

The DLP® 3D ready Acer P1203 projector presents lifelike and breathtaking visuals for remarkable SMB/classroom presentations. Convenient utilities make this projector easy to set up, while advanced power-management solutions conserve energy and the Earth's resources.

### Why P1203 Projector?

- DLP® 3D ready
- Resolution Native XGA (1,024 x 768)  
Maximum UXGA (1,600 x 1,200),  
1080p (1,920 x 1,080)
- Contrast Ratio 3700:1
- Brightness 3,100 ANSI Lumens (Standard),  
2,480 ANSI Lumens (ECO)
- Projection Distance 3.3' (1.0m) ~ 39' (11.9m)



# Technical Specification

<b>Model Name</b>	P1203 DLP® 3D Ready
<b>Resolution</b>	Native XGA (1,024 x 768) Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
<b>Computer Compatibility</b>	IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
<b>Video Compatibility</b>	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
<b>Aspect Ratio</b>	4:3 (Native), 16:9
<b>Contrast Ratio</b>	3700:1
<b>Displayable Colours</b>	1.07 Billion Colours
<b>Brightness</b>	3,100 ANSI Lumens (Standard), 2,480 ANSI Lumens (ECO)
<b>Projection Lens</b>	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus
<b>Projection Screen Size</b>	23" (58cm) ~ 300" (762cm)
<b>Projection Distance</b>	3.3' (1.0m) ~ 39.0' (11.9m)
<b>Throw Ratio</b>	50"@2m (1.95 ~ 2.15:1)
<b>Horizontal / Vertical Scan Rate</b>	30k ~ 100k Hz / 50 ~ 120 Hz
<b>Lamp Type / Life</b>	Osram 230 W user replaceable P-VIP lamp 2,500 Hours (Standard), 4,000 Hours (ECO)
<b>Keystone Correction</b>	+/-40 Degrees (Vertical), Manual & Auto
<b>Projection Mode</b>	Front, Rear, Front-Ceiling, Rear-Ceiling
<b>Ceiling Mounting Capability</b>	Yes
<b>Audio</b>	One Internal Speaker with 2 watts Output
<b>IR Remote Control</b>	IR remote control with laser pointer & PgUp/PgDn functions
<b>Digital Zoom</b>	2X
<b>Power Supply</b>	AC input 100~240V auto-switching power supply
<b>Power Consumption</b>	290W Watts (Operation), <1 Watts (Standby)
<b>Operating Temperature</b>	5°C ~ 35°C / 41°F ~ 95°F
<b>Noise Level</b>	34 dBA (Standard mode), 31 dBA (ECO mode)
<b>Input Interface</b>	Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1, S-Video (Mini DIN) x 1, HDMI (Video, Audio, HDCP) x 1, PC Audio (Stereo mini jack) x 1
<b>Output Interface</b>	Analog RGB (D-sub) x 1, PC Audio (Stereo mini jack) x 1
<b>Control Interface</b>	USB (Type B) x 1, RS232 (Mini DIN) x 1, 12V DC (Screen control) x 1
<b>Dimensions</b>	269 x 206 x 84 mm (10.6" x 8.1" x 3.3")
<b>Compliance</b>	C-Tick (AS/NZS 60950)
<b>Standard Accessories</b>	AC power cord, VGA cable, Remote control, Battery x 2 for remote control, Lens cap, Carrying case, User's guide (CD-ROM), Quick start guide, Security card
<b>Standard Warranty</b>	2 year return to base

Product specifications are subject to change without prior notice. Acer & the Acer logo are registered trademarks of Acer Inc., and Acer America Corp. All other products, brand names, or company names are trademarks & registered trademarks of their respective companies. Acer shall not be liable for technical, editorial or pictorial errors, inaccuracies or omissions contained herein; nor for any consequential damage resulting from the furnishing, performance, or use of this material. \* Maximum hours. Actual hours depend on usage and configuration. \*\* Contact Acer for warranty details.