

2500/2000 LUMENS ● WXGA/XGA ● ULTRA SHORT THROW PROJECTOR

PDG-DWL2500/DXL2000

WXGA/XGA ULTRA SHORT THROW PROJECTOR



DLP



Built-in Network



Ultra Short-Throw



Closed Caption



3D Ready

THE WORLD'S SHORTEST PROJECTION DISTANCE

Project a large 80" diagonal image from the world's shortest projection distance of about 13 inch is achieved by a newly developed ultra short-focus mirror optical system. This projector makes it perfect for giving effective lectures or presentations in educational settings. A maximum projected image size of 110" diagonal and this projector allows it to be placed in a variety of locations including table tops, walls, ceiling, or floors.

As of June 2010

LARGE-SCREEN 3D PROJECTION CAPABILITY

The "Frame Sequential Display Format" a technology that rapidly alternates between left-eye and right-eye images for 3D technology enables the viewing of 3D images when wearing 3D glasses.²

² 3D glasses (sold separately) are required in order to view projected images in 3D. (DLP Link and IR formats compatible.)

NETWORKING CAPABILITY

The PDG-DWL2500/DXL2000 is equipped with SANYO's exclusive PJ Network Interface for wired networking. A common feature among SANYO's extensive line of commercial projectors. Networking allows the monitoring of projector functions and operation from a long distance via a web browser. Emails can be sent automatically to report operating status.

ALMOST MAINTENANCE FREE

This projector offers long periods of maintenance-free use, without the need for lamp replacement, and filter replacement. The PDG-DWL2500/DXL2000 is equipped with SANYO's proprietary hybrid filter composed of multiple filter layers, and the lamp life has been improved compared to conventional models. The longer lamp lifespan and long life filter saves time and money.

COMPACT DESIGN FOR SAVING SPACE IN INSTALLATION

A newly developed single chip DLP format optical engine makes the projector more compact.

CLOSED CAPTION

The PDG-DWL2500/DXL2000 is Closed Caption compatible.



PRESENTATION TECHNOLOGIES

21605 Plummer Street
Chatsworth, CA 91311
Ph: 888-337-1215 (toll-free)
Fax: 818-717-2719
www.sanyoprojectors.com

PDG-DWL2500

PDG-DXL2000

Resolution	WXGA (1280 x 800)	XGA (1024 x 768)
Brightness (typical)	2500 Lm	2000 Lm
Contrast Ratio (Full on / off)	2000:1	
Image Size	60"-110"	55"-90"
Aspect Ratio	16:10	4:3
Projection Lamp	275W	
Scanning Frequency	TBD	
Fan Noise	TBD	
Voltage	100-240V AC ; 50/60 Hz	
Power Consumption	TBD	TBD
Input signal compatibility	WUXGA, WXGA, UXGA, SXGA+, XGA, SVGA, VGA, Mac Analog: 480i/p, 575i/p, 720p(50/60), 1080i(50/60) HDMI : 480p, 575p, 720p(50/60), 1080i/p(50/60)	
Color System	NTSC, PAL, SECAM, NTSC4.43, PAL-M/PAL-N	
Projection Lens (inch)	F 2.50 f=0.19"	
Throw Ratio	N/A	
Throw Distance (feet)	N/A	
Zoom / Focus	Fixed/Manual	
Up / Down Ratio	N/A	
Digital Keystone Correction	V +/- 5°	
Digital Zoom	4x - 1/4x	
Speaker Output	10W	
Weight (lbs)	14.3 lbs	
Dimensions (inch) W,H,D	12.6"x7.0"x15.2"	
Replacement Lamp	# 610 351 3744	
Replacement Remote	# 645 103 3048	
Filter hour* (hour)	TBD	
Lamp Life* (hour)	TBD	
Input	PC/Video	D-sub 15 x 1 (RGB, Component) D-sub 15 x 1 (RGB, Monitor out) Mini DIN 4pin x 1 (S-Video) RCA x 1 (Composite) HDMI x 1 (Ver.1.3)
	Audio	Stereo mini jack x 1 RCA x 2(R/L, mono)
Output	PC/Video	D-sub 15 x 1 (in common)
	Audio	Stereo mini jack x 1
Other Feature	D-sub 9pin x 1 (control port) RJ-45 x 1 (Wired LAN) Mini-DIN 3-pin x 1 (3D SYNC OUT)	
Included Accessories	Power cord	Quick reference guide
	VGA cable Lens cap	Owner's manual (CD-ROM) Remote control
Optional Accessories	POA-COMPVGA	(Component - VGA cable)
	POA-CA-SCART	(Scart - VGA cable)
Warranty	Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty	

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

* Lamp life may vary due to room conditions, usage, and maintenance. The replacement time is a general estimate. The brightness of a lamp usually decreases over time and use.



Back Panel