

P7203 PROJECTOR

DLP Technology – Professional Series

Acer P7203 professional projector is equipped with advanced technologies and convenient setup utilities to deliver clear, persuasive presentations in large business venues.

Why a P7203 Projector?

- Native XGA (1,024 x 768)
Maximum UXGA (1,600 x 1,200),
1080p (1,920 x 1,080)
- Contrast Ratio 3200:1
- Brightness 5,000 ANSI Lumens (STD), 4,000 ANSI Lumens (ECO)
- Projection Distance 3.3' (1.0m) ~ 31.0' (9.4m)
- Picture-in Picture support
- True 24p feature



Technical Specification

Model Name	P7203
Resolution	Native XGA (1,024 x 768) Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Computer Compatibility	IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Contrast Ratio	3200:1
Displayable Colours	1.07 Billion Colours
Brightness	5,000 ANSI Lumens (Standard), 4,000 ANSI Lumens (ECO)
Projection Lens	F = 2.45 ~ 2.9, f = 22.18mm ~ 33.27mm 1:1.5 Manual Zoom and Manual Focus
Projection Screen Size	21" (53cm) ~ 300" (762cm)
Projection Distance	3.3' (1.0m) ~ 31.0' (9.4m)
Throw Ratio	64"@2m (1.55 ~ 2.36:1)
Horizontal Scan Rate	30k ~ 100k Hz
Vertical Scan Rate	50 ~ 85 Hz
Lamp Type / Life	Philips 350 W user replaceable P-VIP lamp / 1,500 Hours (Standard), 2,500 Hours (ECO)
Keystone Correction	+/-40 Degrees (Vertical), +/-15 Degrees (Horizontal), Manual
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Ceiling Mounting Capability	Yes
Audio	Two Internal Speaker with 3 watts Output
IR Remote Control	IR & wired remote control with laser pointer & mouse & PgUp/PgDn functions
Digital Zoom	8X
Power Supply	AC Input 100-240V auto-switching power supply
Power Consumption	460 Watts (Operation), 1 Watt (Standby, LAN off)
Operating Temperature	5°C ~ 35°C / 41°F ~ 95°F
Noise Level	34 dBA (Standard mode), 29 dBA (ECO mode)- w/o dust filter
Input Interface	Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, Component (3 RCA) x 1, HDMI (Video, Audio, HDCP) x 1, DVI (HDCP) x 1, PC Audio (Stereo mini jack) x 2, USB (Type A) x 2, USB (Mini B) x 1
Output Interface	Analog RGB (D-sub) x 1, PC Audio (Stereo mini jack) x 1, SPDIF Audio (RCA) x 1
Control Interface	USB (Type B) x 1, RS232 (Mini DIN) x 1, Wired remote control port (Mini jack) x 1, 12V DC (Screen control) x 1
Weight and Dimensions	16.5 lbs (7.5Kg) / 398 x 310 x 130 mm (15.7" x 12.2" x 5.1")
Compliance	C-Tick (AS/NZS 60950)
Standard Accessories	AC power cord, VGA cable, Composite video cable, DVI cable, S-Video cable, Component cable, Remote control, Battery x 2 for remote control, Duster filter x 2, Lens cap, Carrying case, User's guide (CD-ROM), Quick start guide, Security card
Standard Warranty	2 year return to base

Product specifications are subject to change without prior notice. Acer & the Acer logo are registered trademarks of Acer Inc., and Acer America Corp. All other products, brand names, or company names are trademarks & registered trademarks of their respective companies. Acer shall not be liable for technical, editorial or pictorial errors, inaccuracies or omissions contained herein; nor for any consequential damage resulting from the furnishing, performance, or use of this material. * Maximum hours. Actual hours depend on usage and configuration. ** Contact Acer for warranty details.