

## D9 series

additional HDMI, RJ45




### Easy Lamp Replacement

**sliding top cover:**  
Convenient top loading allows for quick and easy lamp replacement.

### Password management system

In order to improve the security and confidentiality, D9 series is equipped with a password management system, can be configured to verify password and boot time projector. The user-friendly management of the projector can improve its efficiency. At the same time, in the absence of input signal source when the user set the time automatically shutdown, not only saves energy, but saves user's cost.

### Filter Free Say NO to the anti-dust filter



Unlike other technology based projector with anti-dust filter which optics device is exposed in the air that causes temperature

increment. However, DLP based projector has the congenital superiority in against dust aspect. Vivitek D9 series has sealed pure metal optics engine, which keeps filter free, and more durable in comparison with plastic components

### Network Control



Vivitek the D9 series can monitor and control projector by network, so that managers in the control room to be able to manage the projector effectively.

### Environmental Protection RoHS COMPLIANT

Vivitek Technology always pays attention to the environmental protection & energy saving. The D9 contains following parts that is RoHS compliant:

- ▶ Hi-efficiency power switching: reduces power consumption
- ▶ Recycled paper: used in the user manuals and packing cartons
- ▶ Less than 1w power consumption in standby mode, conforms to the
- ▶ Lead-free solder: used for soldering all parts including circuit component electronics
- ▶ Lead-free glass: used for the lens

### Full Connectivity




D9 series has 2 built-in VGA input, and a VGA out-put.

At the same time, it also has a RJ45 network interface and high-definition version of HDMI 1.3 digital imaging terminal. The wide range of input and output interfaces also increased the ease of use.



### Double anti-theft

In addition to the password settings, D9 series has double anti-theft feature, under the provision of anti-theft, anti-theft devices available to hardware. Strengthen the integration of anti-theft bar, the user can use the safety chain to fixed the projector. At the same time D9 is also equipped with the Kensington security lock bolt.



### Specification

MODEL	D930TX	D935VX	D940VX
Display Technology	0.55" 1-Chip DMD	0.55" 1-Chip DMD	0.7" 1-Chip DMD
Resolution	XGA1024x768 / UXGA1600x1200		
Brightness	3,000 Lumens		4300 Lumens
Contrast ratio	2,400:1		
Projection distance	0.5~5 M	1~10 M	
Projection screen size	38"-380"	22.5"-300"	23.4"-300"
Remote control	Fully Featured IR Remote with Laser Pointer and Mouse		
Lamp	280W	230W	280W
Aspect ratio	Native (4:3) & Compatibility (16:9)		
PC Compatibility	VGA, SVGA, XGA, WXGA, SXGA, UXGA, Macintosh		
Video compatibility	EDTV (480p), HDTV (480i/p, 720p, 1080i, 1080p)		
	SDTV 480i/p, NTSC/NTSC 4.43, PAL B/G/H/M/N 60, SECAM		
PC input terminals	HDMI (ver.1.3) x 1, VGA (D-Sub 15 pin) x 2, Composite Video (RCA x 1) S-Video (Mini DIN) x 1, Audio(RCA Stereo) x 1, Audio(Mini-Jack) x 1		
Output terminals	VGA (D-Sub 15 pin) x 1, Audio(Mini-Jack) x 1		
Communication Terminals	USB (Service), RS-232C x 1, RJ45 x 1		
Keystone correction	Vertical (+/- 15 degree		
Fan noise level	3W Speaker		
Audio speaker	34dB/37dB	29dB/34dB	34dB/37dB
Projection method	Front, Rear, Table Top and Ceiling Mount		
Dimensions (wtxhxd)	335x102x256 mm (13.2" x 4" x 10")		
Weight	3.6 kg	3.5 kg	3.5 kg
Power supply	AC 100-240V		
Power consumption	350W, standby < 1W	290W, standby < 1W	350W, 待机 < 1W
Accessory	AC Power Cord, VGA-VGA Cable, Batteries for Remote, User Manual(CD), Remote Control, Lens Cap, Carrying Case		
Osd language	English/French/German/Italian/Spanish/Korean/Hungarian Simplified Chinese/Traditional Chinese/ Russian/Greek /Czechoslovak/Portuguese/Polish/Finnish/Swedish/Dutch /Danish/Turkish/Arabic/		



D930TX



D935VX/D940VX

**D935VX/D940VX .. High Brightness Projector**


**D930TX..SHORT-THROW**

**76" Diagonal @ 1 m . 100" Diagonal @ 1.3 m**

High Brightness Short-Throw projector providing versatility for wide range of applications for instance in class rooms together with interactive wide boards or in small meeting rooms



# D9 series



► With OSRAM's latest high-power long-life light bulbs and sealed optical engine design, created a high-performance and high stability products. Vivitek D9 series gives user a worry-free experience with its high Quality.

## High Stability

new lamp increased stability



Every user realizes that light bulb is one of the significant part of projector. Lamp life and projection quality will be influenced seriously by using flaw lamp. Vivitek Technology cooperate with Osram, world's top lamp manufacturer, develops new generation high efficient lamp last for up to 4,000 hours in Eco mode yet remains high stability.



\*D935VX Lamp Life can be 4000 hours In Eco Mode, D940VX/D930TX: 3000 hours.

## 3:2 2:2 Pull Down



D9 Series with 3:2 / 2:2 Pull Down Technology, can effectively reduce the "sawtooth" of dynamic image, and make images more smooth.

## High Brightness Are you tired of dim image? excellent improved image with high brightness



Market demand for high brightness increases gradually, the benefit from high brightness can achieve better result if the presenter wants eye contact with the audience while keeps ambient light on.

## Instant on & off standby power ≤ 1w


Instant hot re-start means the user, as compare to lamp projector, don't need to wait for minutes to cool the lamp before re-start the projector.

## Stunning picture quality

VividWheel III-enhanced Color Reproduction



► Improve color reproduction. Enabled Video AGC (Automatic Gain Control) for Video Source  
 ► With enabled automatic gain control, you will enjoy an essentially constant output signal from an electronic circuit despite variations in the strength of the input signal



# D930TX SHORT-THROW 76" Diagonal @ 1 m . 100" Diagonal @ 1.3 m


## Small space to show large picture



► Projection free space, do not need large conference space, meeting in their own small office space. Meeting can start at any time to discuss freely!



► Eliminates shadows on the screen along with projected light in the presenter's eyes.





► Significantly reduce the shadow of the briefing, to see more clearly.




## Big Screen — Short Distance

On many occasions does not give users a very spacious room for projection display. Vivitek introduced the wide-angle lens of 930TX short-throw projector. High-precision short focal lens enables the clear focus of projection images without any fuzzy edge or deformation focus.



## Projection Size & Distance



D930TX	40	76	80	100	120	150	300
Screen Size (inch)	40	76	80	100	120	150	300
Distance(M)	0.53	1	1.05	1.32	1.58	1.98	3.95
Height (M)	0.61	1.1	1.22	1.52	2.1	2.63	4.57

D935VX	TELE			Wide		
Screen Size (inch)	30	80	200	40	100	300
Distance(M)	1.34	3.58	8.94	1.54	3.86	11.58
Height (M)	0.46	1.22	3.05	0.61	1.52	4.57

D940VX	TELE			Wide		
Screen Size (inch)	30	80	200	40	100	300
Distance(M)	1.28	3.41	8.53	1.46	3.66	10.97
Height (M)	0.46	1.22	3.05	0.61	1.52	4.57

The above numbers are approximate, and may be slightly different from the actual measurements