















D5 Series

Thanks to its BrilliantColor technology and 2600 lumens of ultra brightness, this compact and lightweight short throw mobile DLP projector is perfect for business or home use, where limited space is concerned.

Vivitek **D5** series professional data projector


	D520	D525		
Display technology	0.55" 1-Chip DMD	0.55" 1-Chip DMD		
Resolution	Native SVGA 800 x 600	Native XGA 1024 x 768		
Brightness	2600 ANSI Lumens	2600 ANSI Lumens		
Contrast ratio	2300:1			
Zoom & focus	Fixed Zoom & Manual Focus	Manual Zoom & Manual Focus		
Lens throw ratio	0.9	0.9~0.99		
Projection screen size	55"@1m	44"-300"		
Remote control	Business Card Type Remote Control			
Lamp	240W (STD), 180W (ECO)	240W (STD), 180W (ECO)		
Aspect ratio	Native (4:3) & Compatibility (16:9)			
PC compatibility	VGA, VXGA, SVGA, XGA, SXGA, UXGA, Macintosh			
Video compatibility	EDTV (480p), HDTV (576i/p, 720p, 1080i), NTSC/NTSC 4.43, PAL			
	B/G/H/I/M/N 60, SECAM			
Input terminals	HDMI v1.3x 1, VGA (15pin D-Sub)x 1, Composite Video (RCA)			
	S-Video (Mini DIN)x 1, Audio Min	i-Jackx1, Stereo Audio (RCA)x 1		
Communication terminals	RS-232C x 1			
Keystone correction	Vertical (+/- 15 degree)			
Fan noise level	35 dB (Standard Mode), 29dB (Eco-Mode)			
Audio speaker	1W Mono			
Projection method	Front, Rear, Table Top and Ceiling Mount			
Dimensions (wxhxd)	261 x 78 x 197mm(10.3" x 3" x 7.8")			
Weight	19 Kg (4.2 lbs)			
Power supply	AC 100-240V			
Power consumption	300W(STD), < 1W Standby Power			
Osd language	English/French/German/Italian/Spanish/Korean/Russian			
	Simplifed Chinese/Traditional Chinese/ Norwegian			
	Czechoslovak/Portuguese/Polish/Swedish/Greek/Dutch			
	Danish/Turkish/Arabic/Hungarian/Finnish			


 $^{^{\}star}$ Specifications are subject to change without prior notice.


Projection Distance

Dimension

Screen size (inch)	Projection Distance Tele (M)	Height (M)	Screen size (inch)	Projection Distance Wide (M)	Height (M)
30	1.32	0.46	40	1.57	0.61
80	3.51	1.22	80	3.14	1.22
100	4.39	1.52	100	3.92	1.52
120	5.27	1.83	120	4.71	1.83
150	6.58	2.29	150	5.88	2.29
200	8.78	3.47	200	7.84	3.47
300	13.17	5.21	300	11.77	5.21







Vivitek Corporation





► Presentation Timer:

Presentation Timer is a user-friendly, flexible timer offered with D5 series to help managing time during presentations.

► Keypad Lock:


Keypad Lock prevents from the embarrassment by pressing keypad accidentally.

► 3:2/2:2 Pulldown:

D5 series supports film cadence detection providing 3:2/2:2 lock time, eliminating jagged images from interlaced video and ensuring crispy clean image quality.

▶ 7 Color Adjustment:

Up to 7 color (Red, Green, Blue, Cyan, Magenta, Yellow, and White) adjustment for preferred color image. Each color adjustment contains Hue/Saturation/Gain from 0 up to 100, a wide selection for best possible image.



► Pre-set Enhanced Display Mode:

up to 7 display mode (Presentation, Bright, Game, Movie, TV, sRGB, and User) to choose from for the best preferable display mode.

► Best Energy Saving:

Less than 1W in Standby Mode for energy saving.

► Close Caption:

Showing text information in NTSC format

> Homi

Latest version 1.3 for enhanced high speed video and audio transferring.

Various I/O connectivity





Http://www.vivitek.org

© 2009 Errors an

© 2009 Vivitek Corporation, Values, Weights and dimensions shown are approximate. Errors and omissions accepted. Specification are subject to change without prior notice. This product maybe subject to export regulations. vivited Is trademark of Vivitek Corporations. Projection images simulated.