



Mobile Performance Meets Style and Versatility

The Vivitek D530 and D535 digital projectors are distinctive in design, lightweight and packed with user-friendly features. Connectivity options for the D530/D535 including HDMI v1.3 and both projectors are 3D-ready, make them ready for the latest multimedia applications. With a high brightness level of 3200 lumens and a weight of only 4.2 lbs, the Vivitek D530 and D535 are the portable solutions to deliver sharp, vibrant pictures and presentations.

Features

- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- High-efficiency lamps that last up to 4000 hours (in economy mode)
- Native SVGA/XGA Resolution and able to display up to UXGA (1600 x 1200)
- Keypad lock feature to avoid accidental change to the setting
- Closed caption and 3D-ready
- Rapid on/off feature
- Enhanced color and display adjustments
- 3200 lumens of brightness with a 2300:1 contrast

Specifications	
Brightness	3200 Lumens
Native Resolution	D530: SVGA (800 x 600), D535: XGA (1024 x 768)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	2300:1 (Full On/Off)
Lamp Life and Type	≈3000/4000 Hours (Standard/Economy Mode), 240W
Lamp Part #	5811116310
Display Type	Single 0.55" DLP® Technology by Texas Instruments
Throw Ratio	1.93 to 2.16:1 (Distance/Width)
Image Size (Diagonal)	23" to 255" (0.6 to 6.5 m)
Projection Distance	3' to 30' (0.9 to 9.1 m)
Projection Lens	F= 2.52–2.73, f= 21.8–24 mm
Zoom Ratio	1.1:1 Manual Zoom/Focus
Aspect Ratio	4:3 Native, 16:9 Compatible
Offset	114%
Keystone Correction	±30° Vertical
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 91.4 KHz
Vertical Scan Rate	43 to 87 Hz
Speaker	1 Watt
Remote Control	Card Type IR Remote
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (480i), EDTV (480p), HDTV (576i, 720p, 1080i) thru RGB, NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Connection Ports	HDMI v1.3, VGA-In, Composite Video, S-Video, Audio RCA L/R, Audio Mini-Jack, RS-232c, USB (Service)
Security	Kensington® Lock Port
Weight	4.2 lbs (1.9 Kg)
Dimensions (W x H x D)	10.3" x 3.0" x 7.8" (261.6 x 76.2 x 198.1 mm)
Noise Level	35dB/29dB (Standard/Economy Mode)
Power	Supply: AC 100-240V Consumption: 180W (Economy Mode), 240W (Standard Mode), <1W (Standby Mode)
Operating Temperature	41 to 104°F (5 to 40°C)
Warranty	1-Year Limited Warranty, 90-Day Lamp Warranty
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, User's Manual(CD), Lens Cap, Warranty Card
Optional Accessories	Replacement Lamp, Remote, Carrying Case
UPC	8 14964 33466 4/8 14964 33467 1 (D530/D535)

