

Dell Micro-portable Projectors 1100MP, 2300MP, 3400MP and 5100MP



Dell | Projectors

**Great things come in small packages,
and they keep getting better.**



Dell 1100MP Projector

Whether for business, education or personal use, Dell™ projectors offer great performance at an affordable price. They are packed with the latest technology and include all the extras as standard, so you have everything you need to get up and running, right out of the box – custom-fitted hard-foam carrying case*, remote control and data/video cables.

Deliver bright, clear images

Dell projectors use advanced DLP™ (Digital Light Processing™) technology from Texas Instruments to achieve great picture quality in a small and light form factor. They combine consistent brightness and high contrast ratios to produce clear, sharp video and text images. With integrated digital keystone correction and zoom capabilities, you can adjust the projector for optimal viewing in almost any situation. Dell offers a choice of native resolutions so you can select the projector to match your user needs and budget.

Outstanding ease of use

Dell Projectors are extremely easy to use. With support for a wide range of video and television input sources and video standards, you get great presentation flexibility. Featuring automatic synchronisation, the projector detects the type of input and changes its settings accordingly. This plug-and-play technology makes the projectors compatible with most computers, including Dell Latitude™ and Inspiron™ notebooks – just follow the simple Quick Setup guide and you're ready to go.

Excellent mobility features

Dell projectors are small and light – they weigh less and are more portable than many notebook computers. They're built for durability, with a sturdy magnesium-alloy casing and include a custom-fitted, hard-foam carrying case*, making travelling light and easy. With desktop or ceiling mount capability and front and rear projection, you can use these projectors just about anywhere.

Perfect for work and entertainment

Dell projectors have enough performance features to be your workhorse during the week and entertainment partner over the weekend. Compliment your home entertainment system by watching movies, sporting events, viewing photos or even playing video games on the big screen.

Great value is a given – it's from Dell!

Like all Dell products, Dell projectors maximise features and performance, while being affordably priced and backed by Dell service and support. Valuable extras, such as a carrying case* and remote control, are included at no extra charge.

* Carrying case available as optional extra for 5100MP projector.



Dell 2300MP Projector



Dell 3400MP Projector



Dell 5100MP Projector


Presentations made easy. Easy as **DELL™**

Visit www.euro.dell.com for more information.

Dell Micro-portable Projectors 1100MP, 2300MP, 3400MP and 5100MP



DLP™ technology by Texas Instruments offers crystal-clear images with superior quality.



Model Name

User Benefits

Projection Technology

Brightness

Native Resolution

Max. Sync Resolution

Contrast Ratio

Displayable Colours

Image Adjustment

Projection Lens

Zoom

Keystone Correction

Projection Screen Size

Projection Distance

Video Compatibility

Horizontal Frequency

Vertical Frequency

Noise Output

Internal Loudspeaker

Bulb Type

Bulb Lifetime

Power Supply

Power Consumption

Power Saver Shutdown

I/O Connectors

Power

Computer Input

Monitor Loop-through

Video Input

Audio Input

Control Input/Output

Environmental

Operating Temperature

Operating Humidity

Storage Temperature

Storage Humidity

Flexible orientation

Included Accessories

Optional Accessories

Weight

Dimensions (w x h x d)

Warranty

	1100MP	2300MP	3400MP	5100MP
Model Name	1100MP	2300MP	3400MP	5100MP
User Benefits	Great features, incredible value	Outstanding value and performance	Ultra-portable, light and bright	High-performance features and connectivity
Projection Technology	Single chip DLP™ DDR technology	Single chip DLP™ DDR technology	Single-chip DLP™ DDR technology	Single-chip DLP™ DDR technology
Brightness	1400 ANSI Lumens (max) ¹	2300 ANSI Lumens (max) ²	1500 ANSI Lumens (max) ³	3300 ANSI lumens (max.) ⁴
Native Resolution	SVGA (800 X 600)	XGA (1024 X 768)	XGA (1024 X 768)	SXGA+ (1400 x 1050)
Max. Sync Resolution	SXGA+ (1400 X 1050)	UXGA (1600 X 1200)	UXGA (1600 X 1200)	UXGA (1600 x 1200)
Contrast Ratio	2100:1 (Full On/Full Off)	2100:1 (Full On/Full Off)	2100 :1 (Full On/Full Off)	2500 :1 (full on/full off)
Displayable Colours	16.7 million	16.7 million	16.7 million	16.7 million
Image Adjustment	Zoom, focus and auto vertical keystone controls	Zoom, focus and vertical keystone controls	Zoom, focus and auto vertical keystone controls	Zoom, focus and auto vertical keystone controls
Projection Lens	F/2.5, f=28.8mm-34.5mm	F/2.4-2.7, f=28.0mm-33.6mm	F/2.7-2.88, f=28.43mm-32.73mm	F/2.6-2.87, f=39.1mm-46.92mm
Zoom	1.2x manual zoom	1.2x manual zoom	1.15x manual zoom	1.2x manual zoom
Keystone Correction	Auto Vertical	Manual Vertical	Auto Vertical	Advanced horizontal and automatic vertical keystone adjustment
Projection Screen Size	0.7m – 7m (diagonal)	0.6m – 7.4m (diagonal)	0.8m – 6.3m (diagonal)	0.6m-7.4m (diagonal)
Projection Distance	1.2m – 10m	1.2m – 12m	1.5m – 10m	1.5m-12m
Video Compatibility	NTSC, NTSC 4.43, PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L) and HDTV (480i/P, 576i/P, 720P and 1080i) compatible	NTSC, NTSC 4.43, PAL, SECAM (B/D/G/K/K1/L) and HDTV (480i/P, 576i/P, 720P, 1080i)	NTSC, NTSC 4.43, PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L) and HDTV (480i/P, 576i/P, 720P, 1080i) compatible	NTSC, NTSC 4.43, PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L) and HDTV (480i/P, 576i/P, 720P, 1080i) compatible
Horizontal Frequency	15kHz – 70kHz	15kHz – 70kHz	15kHz – 80kHz	Analogue: 15kHz-100kHz; Digital: 30kHz-64kHz
Vertical Frequency	43Hz – 85Hz	56Hz – 85Hz	50Hz – 85Hz	Analogue: 43Hz-120Hz; Digital: 43Hz-85Hz
Noise Output	33.8 dBA (normal operation) 31.9 dBA (eco-mode)	38 dBA (normal operation) 34 dBA (eco-mode)	38 dBA (normal operation), 36 dBA (eco-mode)	37dBA (normal operation) 31dBA (eco-mode)
Internal Loudspeaker	One 2-watt speaker	One 2-watt speaker	One 1-watt speaker	Two two-watt speakers
Bulb Type	200-watt, user-replaceable P-VIP bulb	200-watt, user-replaceable P-VIP bulb	156-watt, user-replaceable P-VIP bulb	300-watt, user-replaceable UHP bulb
Bulb Lifetime	2000 hours (up to 2500 hours in Eco-Mode)	2000 hours (up to 2500 hours in Eco-mode)	3000 hours (up to 4000 hours in Eco-mode)	1700 hours (up to 2200 hours in eco-mode)
Power Supply	Universal 100-240V AC, 50-60Hz	Universal 100-240V AC, 50-60Hz	Universal 100-240V AC, 50-60Hz	Universal 90-240V AC, 50-60Hz with PFC input
Power Consumption	250W at normal operation	250W at normal operation	195W at normal operation	400W at normal operation (335W in eco-mode)
Power Saver Shutdown	Yes	Yes	Yes	Yes
I/O Connectors				
Power	AC power input socket	AC power input socket	AC power input socket	AC power input socket
Computer Input	15-pin D-sub for analogue RGB/component, HDTV	15-pin D-sub for analogue RGB/component, HDTV	One M1-DA for analog / digital / component, HDTV input signals	One M1-DA for analogue/digital/component, HDTV input signals, one 15-pin D-sub for analogue input/component, HDTV input signals, one BNC R/G/B/H/V for analogue RGB input signals
Monitor Loop-through	One 15-pin D-sub	One 15-pin D-sub	None	One 15-pin D-sub
Video Input	One composite video (RCA), one RGB/component (via DB 15) and one S-Video	One composite video (RCA), one RGB/component and one S-Video	One Composite video (RCA), one S-Video and one M1-DA for component HDTV	Three RCA connectors for component video/HDTV input, one mini-DIN 4-pin S-video input, one RCA jack for composite video input
Audio Input	One 3.5mm phone jack for line audio input	One 3.5mm phone jack for line audio input	One 3.5mm phone jack for line audio input	One 3.5mm phone mini-jack for line audio input
Control Input/Output	One mini-DIN RS232 input	One mini-DIN RS232 input	None	One mini-DIN RS232 input, one RJ-45 connector for networking, one HDMI input and one 12V DC relay output
Environmental				
Operating Temperature	5°C to 35°C	5°C to 35°C	5°C to 35°C	5°C to 35°C
Operating Humidity	80% maximum	80% maximum	80% maximum	80% maximum
Storage Temperature	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C
Storage Humidity	80% maximum	80% maximum	80% maximum	80% maximum
Flexible orientation	Desktop or ceiling mountable and rear or front projection	Desktop or ceiling mountable and rear or front projection	Front and two rear, desktop adjustable feet and rear or front projection	One front and two rear desktop-adjustable feet
Included Accessories	Carrying bag, Remote Control, Power cord, VGA cable (D-sub to D-sub), S-video cable, USB cable, Composite Video cable, D-sub to YPbPr cable, RCA to Audio cable, mini pin to mini pin cable	Carrying bag, remote control, power cord, VGA cable (D-sub to D-sub), S-video cable, USB cable, Composite Video cable, D-sub to YPbPr cable, RCA to Audio cable, mini pin to mini pin cable	Carrying bag, remote control, power cord, S-video cable, M1 to D-Sub/USB cable, Composite video cable, Mini Pin to Mini Pin cable, RCA to audio cable	Remote control, power cord, S-Video cable, M1 to D-sub/USB cable, composite video cable, mini-pin to mini-pin cable, RCA to audio cable, M1-DA to HDTV cable
Optional Accessories	Ceiling mount kit, replacement bulb kit, Cable kit	Ceiling mount kit, replacement bulb kit, Cable kit	Replacement bulb kit, cable kit, M1-DA to RCA Coax cable kit	Ceiling-mount kit, replacement bulb kit, replacement video cable kit, RS232 cable kit, carrying case, projection screen
Weight	2.2kg	2.13kg	1.09kg	3.72kg
Dimensions (w x h x d)	251mm X 213mm X 101mm	277mm X 93mm X 206mm	204mm X 154mm X 73.7mm	330mm X 115mm X 261mm
Warranty	One year (90 days on bulb)	One year (90 days on bulb)	Two years (90 days on bulb)	Two years (90 days on bulb)

Pricing, specifications, availability and terms may change without notice. Dell's Terms and Conditions of Sales and Service apply and are available on request and at www.euro.dell.com. DLP and Digital Light Processing are trademarks of Texas Instruments, Incorporated. Dell, the Dell logo, Latitude and Inspiron are trademarks of Dell Computer Corporation. 1. Dell 1100MP Projector (1400 max lumens): based on ANSI/NAPM IT7. 228-1997 tests of 73 units, September 2003, with average ANSI Lumens 1406. Bulb brightness degrades with usage. Dell recommends replacing your bulb after 2000 hours of usage. 2. Dell 2300MP Projector (2300 max lumens): based on ANSI/NAPM IT7. 228-1997 tests of 58 units, June 2004, with average ANSI Lumens 2113. Bulb brightness degrades with usage. Dell recommends replacing your bulb after 2000 hours of usage. 3. Dell 3400MP Projector (1500 max lumens): based on ANSI/NAPM IT7. 228-1997 tests of 55 units, April 2005, with average ANSI Lumens 1394. Bulb brightness degrades with usage. Dell recommends replacing your bulb after 3000 hours of usage (up to 4000 hours in Eco-mode). 4. Dell 5100MP Projector (3300 max lumens): based on ANSI/NAPM IT7. 228-1997 tests of 132 units, July 2005, with average ANSI lumens 3307. Bulb brightness degrades with usage. Dell recommends replacing your bulb after 1700 hours of usage (up to 2200 hours in eco-mode). © 2005 Dell Computer Corporation. All rights reserved. Reproduction in any manner whatsoever without the express written permission of Dell Computer Corporation is strictly forbidden.

EU912/11August2005

Presentations made easy. Easy as **DELL™**

Visit www.euro.dell.com for more information.