

CD737x



BRIGHTNESS

3000 ANSI lumens (boost)
2700 ANSI lumens (standard)
2500 ANSI lumens (eco)

RESOLUTION

1024x768 true XGA
1280x1024 SXGA compressed

DISPLAY TYPE

TI DMD 0.7", 12° DDR, DLP chip

CONTRAST RATIO

2000:1

ASPECT RATIO

4:3 Native
16:9 Compatible

LAMP

200 watt OSRAM VIP

LAMP LIFE

2000 hours (boost)
3000 hours (standard)
4000 hours (eco)



Special features of the CD737x include:

User friendly lamp replacement—Top cover access means no need for dismantling the projector to change the lamp.

Custom start-up screen—Download a jpeg file to customize your start-up image.

Three lamp modes—Change your lamp output for varying light conditions and save on lamp life.

Multiple inputs—Connect to multiple peripheral systems at the same time.

Color management—Adjust individual colors as needed.

OPTIONAL ACCESSORIES:

Extended Warranty
Mac Adapter / DVI Adapter
Cable: Audio / VGA / Component / Composite Video
Universal Ceiling Mount / Suspension Pole/ Round Flush Kit
Spare Lamp Module

SHIPS WITH:

Laser Remote Control
User Manual/CD ROM
Power Cord, Lens Cap & Soft Carry Case
USB Mouse, S-Video Cable
DVI/VGA 15 pin Computer Cable

DIAGONAL IMAGE SIZE

37" - 240" inches

PROJECTION LENS

Manual zoom/focus

ZOOM RATIO

1.22:1 Ratio

THROW DISTANCE

4.9' - 26' feet
1.5 - 8 meters

THROW RATIO

1.63 - 2.0 (x screen width)

INPUTS

Component (R,G,B) Mini audio jack
Composite Video (R/L audio) S-Video
DVI - I VGA-in

OUTPUTS

VGA-out, Mini jack audio

COMPATIBILITY

VGA, SVGA, XGA, SXGA, Mac

PROJECTOR CONTROLS

RS232, USB (mouse control)

KEystone

+/- 15° vertical

VIDEO

NTSC, NTSC 4.43, PAL,
SECAM

HDTV / EDTV / SDTV

480i/p, 576i/p, 720p, 1080i

AUDIO

1 X 2 watt speakers

DIMENSIONS (WxDxH)

12.9" x 3.5" x 9.4" inches
32.8 x 8.8 x 23.8 cm

WEIGHT

7.8 lbs / 3.55 Kg

DECIBEL RATING

38 dB (boost) / 36 dB (standard) / 33 dB (eco)

WARRANTY

3 year parts & labor
90 day lamp

FCC CERTIFICATION

Class B

H-SCAN FREQUENCY

Horizontal—15-70 kHz

V-REFRESH RATE

Vertical—50-85 kHz

POWER SUPPLY

110-240 Voltage (auto ranging)

PWR. CONSUMPTION

260 Watts (boost)
250 Watts (standard)
230 Watts (eco)

BOXLIGHT[®]
CORPORATION

19462 Powder Hill Place, Suite 101
Poulsbo, WA 98370

www.boxlight.com
Direct 800.762.5757
International 360.779.7901
Partners 866.688.3636