

PLUS

U2-817 | U2-1200



THE U2 SERIES FROM PLUS OFFERS INCREDIBLY HIGH-POWERED PROJECTORS IN A VERY PORTABLE 5.6 POUND PACKAGE. YOU CAN CHOOSE EITHER 1500 OR 2000 LUMENS OF BRIGHTNESS AND XGA OR SVGA CLARITY.

MEANWHILE, BOTH PROJECTORS BOAST AN INCREDIBLE 3000 HOURS OF REGULAR LAMP LIFE. OR, IF YOU ARE LOOKING TO GET MORE HOURS OUT OF A BULB, YOU CAN CHOOSE "ECO-MODE" WHICH PROJECTS A LOWER BRIGHTNESS AND INCREASES BULB LIFE TO 4000 HOURS.

THE U2S ARE PERFECT FOR ANY CONFERENCE OR CLASSROOM AND THE ENTIRE LINE OF PROJECTORS CONNECTS WITH VIRTUALLY ANY VIDEO SOURCE.

Ultraportable
at just 5.6 lbs.

Up to 2000 ANSI lumens
corner-to-corner brightness

Digital zoom instantly targets and
enlarges the fine print at the touch
of a button

Connects to virtually any computer
or video source

Digital keystone correction

Built-in control panel and wireless
remote control

3000 Hours of lamp life

Eco-mode

Second monitor output (Loop Thru)

HDTV compatible



PLUS Vision Corp.

9610 SW SUNSHINE CT.
SUITE 300
BEAVERTON, OR 97005
800-211-9001 • 503-748-8700
www.plus-america.com

Connect to an additional video monitor
with new Loop-Thru feature.▼

PLUS

U2-817 | U2-1200



Specifications

U2-817

U2-1200

Resolution	SVGA, 800 x 600 pixels	XGA, 1024 x 768 pixels
RGB Signal	SVGA (true) XGA (compressed) VGA (expansion/true)	XGA (true) SXGA (compressed) SVGA/VGA (expansion/true)
Brightness	1500 ANSI lumens	2000 ANSI lumens
Contrast Ratio	1500:1 (Full on/off)	1500:1 (Full on/off)
Aspect Ratio	4:3, supports 16:9	4:3, supports 16:9
Projection Lens	F=2.4-2.6, f=26.5-31.8 mm 1:1.2 manual zoom, manual focus	F=2.4-2.6, f=26.5-31.8 mm 1:1.2 manual zoom, manual focus
Digital Keystone Correction	+/- 30 degrees	+/- 30 degrees
Digital Zoom	10x	10x
Light Resource	200-watt lamp	200-watt lamp
Lamp Life	3,000 hrs./4,000 hrs. (Eco-mode)	3,000 hrs./4,000 hrs. (Eco-mode)
Color Palette	16.7 million colors	16.7 million colors
Projecting Position	Front/rear, table/ceiling	Front/rear, table/ceiling
Projection Distance	3.9-48.5 ft./1.2-14.8 m	3.9-37.7 ft./1.2-11.5 m
Image Size	21"-300" diagonal/.53-7.62 m	27"-300" diagonal/.68-7.62 m
Video Signal	NTSC3.58, NTSC4.43, PAL, PAL_N, PAL_M, PAL60, SECAM, YCbCr (NTSC, PAL), YPbPr (480p, 720p, 1080i)	NTSC3.58, NTSC4.43, PAL, PAL_N, PAL_M, PAL60, SECAM, YCbCr (NTSC, PAL), YPbPr (480p, 720p, 1080i)
Terminal	RGB, DVI, composite and S-video, RGB out	RGB, DVI, composite and S-video, RGB out
Audio	Mono 1-watt	Mono 1-watt
Dimensions Excluding Lens and Stand:		
Height	2.3 in./58 mm	2.3 in./58 mm
Width	9.0 in./230 mm	9.0 in./230 mm
Length	11.7 in./295 mm	11.7 in./295 mm
Weight	5.6 lb./2.5 kg	5.6 lb./2.5 kg

Accessories:

- IR Remote Control
- Power Cable (6 ft./1.8 m)
- VGA Cable (6.5 ft./2 m)
- DVI to mini D-sub 15 pin Adapter
- Video Cable, S-Video Cable (6.5 ft./2 m)
- 3.5 mm mini plug Audio Cable (6.5 ft./2 m)
- 3.5 mm stereo mini jack to RCA Audio Adapter
- Soft Carrying Case

Optional accessories:

- ATA Shipping Case
- Ceiling Mount Kit
- DVI-D Cable (6.5 ft./2 m)
- DVI-I Cable (6.5 ft./2 m)
- VGA Cables (9 ft., 12 ft.)
- User-Replaceable Lamp Unit



Shipping and Carry-on Cases

Keep your projector safe from the rigors of travel with an ATA-certified shipping case. Or take your laptop and projector on the road in one bag with a rolling hard case.



Presentation Screens

Choose from a variety of portable and hanging presentation screens from PLUS. They will save the day when you can't control your presentation environment.



Replacement Bulbs

PLUS offers a wide array of replacement bulbs so you can carry a spare anywhere.



Remote Controls

Choose from a variety of wireless remotes to fit any presentation environment.



PLUS Vision Corp.

9610 SW SUNSHINE CT.
SUITE 300
BEAVERTON, OR 97005
800-211-9001 • 503-748-8700
www.plus-america.com