

PLUS

U4-SERIES



Up to 1,800 ANSI lumens
corner-to-corner brightness

Only 3 pounds

Eco-mode lets you increase
lamp life by 30%

Digital zoom instantly targets and
enlarges the fine print at the touch of
a button

Connects to virtually any computer
or video source

Short-focus lens allows for big-screen
presentations in cramped quarters

Digital keystone correction

Wireless remote control and built-in
control panel

HDTV compatible

CompactFlash card slot available

INTRODUCING THE BRIGHTEST PROJECTORS IN THEIR CLASS: THE 3 LB.

U4 SERIES FROM PLUS. WITH UP TO 1800 LUMENS AND A 2000:1

CONTRAST RATIO, THE U4 SERIES BOASTS IMAGERY THAT'S CRISPER,

CLEANER AND BRIGHTER THAN EVER. THE CEILING-MOUNTABLE U4 ALSO

COMES WITH AN ECO-MODE OPTION THAT LETS YOU SAVE BULB LIFE.

PLUS Vision Corp.

9610 SW SUNSHINE CT.
SUITE 800
BEAVERTON, OR 97005
866-427-8855 • 503-748-8855
www.plus-america.com





U4-SERIES

Specifications	U4-136	U4-232
Resolution	XGA, 1024 x 768 pixels	XGA, 1024 x 768 pixels
RGB Signal	XGA (true) SXGA (compressed) SVGA/VGA (expansion/true)	XGA (true) SXGA (compressed) SVGA/VGA (expansion/true)
Brightness	1500 Lumens	1800 Lumens
Contrast Ratio	1500:1 (Full on/off)	2000:1 (Full on/off)
Aspect Ratio	4:3, supports 16:9	4:3, supports 16:9
Projection Lens	F=2.6-2.9 f=27.5-33mm 1:1.2 Manual Zoom Manual Focus	F=2.6-2.9 f=27.5-33mm 1:1.2 Manual Zoom Manual Focus
Digital Keystone Correction	+25/-35 degrees	+17/-22 degrees
Digital Zoom	10x	2x
Light Resource	150-watt lamp, 1,500 hrs. 2,000 hrs. in Eco-mode	180-watt lamp, 1,500 hrs. 2,000 hrs. in Eco-mode
Color Palette	16.7 million colors	16.7 million colors
Projection Positions	Front/rear, Table/ceiling	Front/rear, Table/ceiling
Projection Distance	3.9-25.9 ft. / 1.2-7.9 m	3.9-38 ft / 1.2-11.6 m
Image Size	26"-200" diagonal	26"-300" diagonal
Video Signal	NTSC3.58, NTSC4.43, PAL, PAL-M, PAL-N, PAL60, SECAM, YCbCr (NTSC, PAL), YPbPr (480p, 720p, 1080i)	NTSC3.58, NTSC4.43, PAL, PAL-M, PAL-N, PAL60, SECAM, YCbCr (NTSC, PAL), YPbPr (480p, 576p, 720p, 1080i)
Audio	Mono 0.5 watt	Mono 0.5 watt
Dimensions Excluding Lens and Stand:		
Height	2.08 in./53 mm	2.08 in./53 mm
Width	7.5 in./190 mm	7.5 in./190 mm
Length	9.4 in./239 mm	9.5 in./242 mm
Weight	3.3 lb./1.5 kg	3.3 lb./1.5 kg

Included accessories:

- Wireless remote control
- Power cable (6 ft./1.8 m)
- Video cable (6.5 ft./2 m)
- S-video cable (6.5 ft./2 m)
- 3.5 mm mini plug audio cable (6.5 ft./2 m)
- 3.5 mm stereo plug to RCA
- DVI to mini D-sub 15 pin (6.5 ft./2 m)
- Soft carrying case
- User's manual
- CompactFlash card 16 MB(U4-136)
- PC Card Adapter (U4-136)

Optional accessories:

- ATA shipping cases
- VGA cables (9-12 ft./2.7-3.6 m)
- DVI-D cable (6.5 ft./2 m)
- 3.5 mm, 4-pole plug to RCA component cable (5 ft./1.5 m)
- 15-pin to RCA component cable (10 ft./3 m)
- Presenter-2-Go - laptop-free presentation system
- Display-to-Go - output DVI from any laptop
- Ceiling mount kit



Presentation Screens

Choose from a variety of portable presentation screens from PLUS. They will save the day in any presentation environment.



Replacement Bulbs

PLUS offers a wide array of replacement bulbs so you can carry a spare anywhere.



Remote Controls

Choose from a variety of wireless remotes to fit any presentation environment.



PLUS Vision Corp.

9610 SW SUNSHINE CT.
SUITE 800
BEAVERTON, OR 97005
866-427-8855 • 503-748-8855
www.plus-america.com