

# PLUS

## U5-SERIES



### VALUE. PERFORMANCE. CHOICE.

THE U5 SERIES IS EVERYTHING A PRESENTER NEEDS FROM A DIGITAL PROJECTOR. FEATURES LIKE A SHORT-FOCUS ZOOM LENS, HDTV COMPATIBILITY AND UP TO 3000 LUMENS ARE AVAILABLE IN THIS COMPACT 4-POUND PACKAGE. LIKE ALL PLUS PROJECTORS, THE U5'S ARE EASY TO USE AND CONNECT TO VIRTUALLY ANY VIDEO SOURCE.

THE U5'S ARE IDEAL FOR PRESENTERS ON THE GO, BOARDROOM USE OR CLASSROOM USE. AND WITH PASSWORD-PROTECTED THEFT PREVENTION, YOU'LL HAVE PEACE-OF-MIND WHEREVER A PLUS PROJECTOR IS NEEDED.

Up to 3000 ANSI Lumens corner-to-corner Brightness

Only 4 pounds

Eco-mode lets you increase lamp life by 30%

8x digital zoom instantly targets and enlarges the fine print at the touch of a button

Connects to virtually any computer or video source

Models featuring short-focus zoom lenses allowing for flexible big-screen presentations in cramped quarters

Anti-theft security

RS-232 Support

HDTV Compatible



### PLUS Vision Corp.

9610 SW SUNSHINE CT.  
SUITE 800  
BEAVERTON, OR 97005  
800-211-9001 • 503-748-8700  
www.plus-america.com

## Remote for U5-111/112



## Remote for U5-132/232

## U5-SERIES

Specifications	U5-111/U5-112	U5-132/U5-232
Resolution	SVGA, 800 x 600 pixels	XGA, 1024 x 768 pixels
RGB Signal	SVGA (true) XGA (compressed) VGA (expansion/true)	XGA (true) SXGA (compressed) SVGA/VGA (expansion/true)
Brightness	1600 ANSI lumens	2000 ANSI lumens
Bright Mode		3000 ANSI lumens monochrome (U5-232)
Contrast Ratio	2000:1 (Full on/off)	2000:1 (Full on/off)
Aspect Ratio	4:3, supports 16:9	4:3, supports 16:9
Projection Lens	F=2.6, f=19 mm (U5-111) Manual Focus (U5-111) F=2.6-2.9, f=20-24 mm (U5-112) 1:1.2 Manual Zoom/Focus (U5-112)	F=2.6-2.9, f=18.4-22 mm 1:1.2 Manual Zoom/Focus
Digital Keystone Correction	20 degrees	20 degrees
Digital Zoom	8x	8x
Light Resource	200-watt lamp, 2,000 hrs. 3,000 hrs. in Eco-mode	200-watt lamp, 2,000 hrs. 3,000 hrs. in Eco-mode
RS-232 Control		9-pin D-sub input terminal
Color Palette	16.7 million colors	16.7 million colors
Projection Positions	Front/rear, table/ceiling	Front/rear, table/ceiling
Projection Distance	3.9-34.7 ft. / 1.2-10.6 m (U5-111) 3.9-36.4 ft. / 1.2-11.1 m (U5-112)	3.9-26.2 ft / 1.2-8.0 m
Image Size	34"-300" diagonal (U5-111) 28"-300" diagonal (U5-112)	38"-300"
Video Signal	NTSC3.58, NTSC4.43, PAL, PAL-M, PAL-N, PAL60, SECAM, YCbCr (NTSC, PAL), YPbPr (480p, 720p, 1080i) Built-in Line Doubler	NTSC3.58, NTSC4.43, PAL, PAL-M, PAL-N, PAL60, SECAM, YCbCr (NTSC, PAL), YPbPr (480p, 720p, 1080i) Built-in Line Doubler
Audio	Mono 0.8 watt	Mono 0.8 watt
Dimensions Excluding Lens and Stand:		
Height	2.3 in./60 mm	2.3 in./60 mm
Width	8.5 in./216 mm	8.5 in./216 mm
Length	9.7 in./246 mm	9.9 in./252 mm
Weight	4.1 lb./1.9 kg	4.4 lb./2.0 kg



### Presentation Screens

Choose from a variety of portable presentation screens from PLUS. They will save the day in any presentation environment.



### Replacement Bulbs

PLUS offers a wide array of replacement bulbs so you can carry a spare anywhere.



### Elmo HX-3000 Visualizer

Allowing you to present 3D objects or documents via PLUS projectors.

#### Included accessories:

- Wireless remote control (U5-111/112)
- Wireless remote control w/ mouse control (U5-132/232)
- Power Cable (6ft./1.8 m)
- VGA cable (mini D-sub 15 pin) (6.5ft./2 m)
- S-video cable (6.5ft./2 m)
- Video cable, RCA (6.5ft./2 m)
- 3.5mm stereo mini plug audio cable (6.5 ft./2 m)
- 3.5mm stereo plug to RCA
- USB cable, Mini-B - Type A (6.5ft./2 m) (U5-132/232)
- Soft carrying case
- User's manual

#### Optional accessories:

- ATA shipping cases
- VGA cables (9 ft., 12 ft.)
- 15-pin to RCA component cable (10 ft./3 m)
- Zen Z2 Remote RF Wireless USB Mouse
- Ceiling mount kit



## PLUS Vision Corp.

9610 SW SUNSHINE CT.  
SUITE 800  
BEAVERTON, OR 97005  
800-211-9001 • 503-748-8700  
www.plus-america.com