ENTERTAINMENT PROJECTOR PJ-TX10

- Flexible Placement
- Enjoy a Large Image from Near to Far
- Without Caring about Noise, You Can Concentrate on the Screen
- Front Air Exhaust for Comfortable Viewing
- Large, Powerful Images with Superb Video Quality
- The Picture You Like, at the Touch of a Button

HITACHI
Inspire the Next

The dynamic power of a theater, right in your living room.

ENTERTAINMENT PROJECTOR

PJ-TX10

HITACHI

With the PJ-TX10, you're always in the best position.





With the PJ-TX10, you're always in the best position.



Flexible Placement


You can easily adjust the position of the image both horizontally or vertically just by turning a dial. Horizontal lens shift lets you move the image right and left, so you can place the projector to the side and sit in the best position in front of the screen. Vertical lens shift adjusts the image up and down, so you can install the projector in a high location in a large room. And because the lens is moved by an optical system, you can adjust the image without the deterioration in picture quality that can be caused by digital compensation.






Enjoy a Large Image from Near to Far

The powerful 2x optical zoom lens allows you to place the projector in the most convenient location in a large room. It can be positioned within a 2.6m to 5.2m range to project a large 100" image.



Without Caring about Noise, You Can Concentrate on the Screen

In whisper mode the PJ-TX10 achieves astonishing low noise of 25dB. This means that even during tense or intimate quiet scenes, you can concentrate on the movie without the distraction of noise from the projector fan.





Front Air Exhaust for Comfortable Viewing

Air is exhausted from the front of the projector, so it doesn't bother viewers. This also allows you to place the projector on an AV rack or bookshelf where air cannot be exhausted from



Large, Powerful Images with Superb Video Quality

Motion adaptive progressive scan provides a smooth picture, less line flicker, and better resolution. 3:2 pull down ensures precise movie reproduction and a 3D Y/C separation IC reduces color noise. The PJ-TX10 will project 16:9 widescreen images with 854 x 480 resolution and accepts 480p DVD signals for outstanding video quality. Contrast ratio is an excellent 800:1.



The Picture You Like, at the Touch of a Button

The projector is capable of memorizing four combinations of color, gamma, color temperature, aspect and overscan settings. Instead of making adjustments each time, you can enjoy optimum video quality with various types of movies at

Assured of the Highest Quality Connection

The PJ-TX10 is equipped with composite, S-Video, component, and RGB terminals for full signal



Stylish Contemporary Design

The PJ-TX10 has an attractively styled pearl silver body that matches any interior. In addition, the rear panel has a cover, giving the unit a neat appearance when not in use.




A Remote Control that's Truly Easy to Use

You can use the remote control to turn the power on and off and change the input signal or picture node with a single touch.




ENTERTAINMENT PROJECTOR PJ-TX1



		Specifications	
Model name		PJ-TX10	
Liquid crystal panel structure		0.55" polysilicon active-matrix TFT x 3	
Number of pixels		409,920 pixels (V480 x H854)	
Resolution		854 x 480 color pixels	
Noise (Whiper mode)		25dB	
Frequency	fн [kHz]	15-91	
	fv [Hz]	50-120	
Lens		Manual zoom (F=1.6-2.8) 1:2.0	
Lamp		130W UHB	
Brightness		700 ANSI Lumens	
Contrast ratio		800 : 1	
Speaker		1W x 1	
Power supply		AC100-120V/AC220-240V	
Operating temperature		0-35°C (32-95°F)	
Input signals	RGB input	VGA, SVGA, XGA, SXGA, MAC13", MAC16"	
	Video input	NTSC, NTSC4.43, PAL, PAL60, SECAM, M-PAL, N-PAL, HDTV: 750p (720p), 1125i (1080i/1035i) SDTV: 525i (480i), 525p (480p), 625i (575i)	
Terminals	Video input	S-Video: Mini DIN 4-pin terminal x 1 Composite video: RCA jack terminal x 1 Component video: RCA jack terminal x 3 Audio: RCA jack terminal x 2 (L/R)	
	RGB input	Analog RGB: D-sub 15-pin shrink terminal x 1 Audio: Stereo mini jack x 1	
	Control terminal	D-sub 9-pin shrink terminal x 1	
Regulatory approvals		UL60950/C-UL, FCC Part 15, Class B, CE, TUV EN60950	
Dimensions (WxHxD)		350x121x285mm (13-3/4"x4-3/4"x11-1/4") [excl. protruding part]	
Weight		3.6kg (7 lbs. 15 oz.)	
Standard accessories		Remote control, Batteries, Power cord, Video cable (for video/audio), Safety instruction, Quick guide, User's manual	


- •Design and specifications are subject to change without notice.
- •The screen picture and comparison photos in this catalog are simulated.
- •LCD panels, polarizors and other optical components and cooling fans may need replacement after prolonged usage





16:9 Screen						
Screen Size (inch)	a Min	a Max	b (top)			
30	0.7m (29")	1.5m (60")	37cm (15")			
40	1.0m (40")	2.1m (81")	50cm (20")			
50	1.3m (50")	2.6m (102")	62cm (25")			
60	1.5m (60")	3.1m (122")	75cm (29")			
70	1.8m (71")	3.6m (143")	87cm (34")			
80	2.1m (81")	4.2m (163")	100cm (39")			
90	2.3m (91")	4.7m (184")	112cm (44")			
100	2.6m (101")	5.2m (205")	125cm (49")			
120	3.1m (122")	6.2m (246")	149cm (59")			
150	3.9m (153")	7.8m (308")	187cm (74")			
200	5.2m (204")	10.4m (411")	249cm (98")			
250	6.5m (256")	13.0m (513")	311cm (123")			
300	7.8m (307")	15.7m (616")	374cm (147")			

4:3 Screen						
Screen Size (inch)	a Min	a Max	b (top)			
30	0.9m (36")	1.9m (74")	46cm (18")			
40	1.2m (49")	2.5m (99")	61cm (24")			
50	1.6m (62")	3.2m (125")	76cm (30")			
60	1.9m (74")	3.8m (150")	91cm (36")			
70	2.2m (87")	4.4m (175")	107cm (42")			
80	2.5m (99")	5.1m (200")	122cm (48")			
90	2.8m (112")	5.7m (225")	137cm (54")			
100	3.2m (124")	6.4m (251")	152cm (60")			
120	3.8m (150")	7.6m (301")	183cm (72")			
150	4.8m (187")	9.6m (377")	229cm (90")			
200	6.4m (250")	12.8m (503")	305cm (120")			
250	8.0m (313")	16.0m (629")	381cm (150")			
300	9.5m (376")	19.2m (755")	457cm (180")			



Hitachi, Ltd. Digital Media Division (Yokohama Plant) has received ISO 14001 certification.





HITACHI

Hitachi Europe Ltd.

Whitebrook Park, Lower Cookham Road, Maidenhead Berkshire, SL6 8YA, UK Tel: +44-1628-643000 Fax: +44-1628-643404 www.hitachidigitalmedia.com

Hitachi Home Electronics (America), Inc.

900 Hitachi way, Chula Vista, CA 91914-3556 Tel: +1-619-591-5200 Fax: +1-619-591-5201 www.hitachi.com

Hitachi Canada Ltd.

6740 Campobello Road, Mississauga, Ontario L5N2L8, Canada

Tel: +1-905-821-4545 Fax: +1-905-821-1011 www.hitachi.ca Hitachi Home Electronics Asia (S) Pte. Ltd.

16 Collyer Quay #31-00 Hitachi Tower, Singapore 049318

Tel: +65-6536-2520 Fax: +65-6536-2521 www.hitachimultimedia.com.sg

Hitachi Sales (Malaysia) Sdn. Bhd.

Wisma Hitachi, No.2, Lorong 13/6A, 46200 Petaling Jaya,

Selangor Darul Ehsan, Malaysia

Tel: +60-3-79573455 Fax: +60-3-79556090

Hitachi Sales (Thailand), Ltd.

994, 996 Sol Thonglor, Sukhumvit 55 Road, Klongton, Klongtoey, Bangkok 10110, Thailand

Tel: +66-2-381-8381 Fax: +66-2-381-9520

Hitachi (Hong Kong), Ltd.

18th Floor, Ever Gain Centre, 28 On Muk Street, Shatin, N.T., Hong Kong

Tel: +852-2113-8883 Fax: +852-2780-4178 www.hitachi-multimedia.com.hk

Hitachi Sales Corp. of Taiwan

2nd Floor, No.65, Nanking East Road, Section 3, Taipei, Taiwan

Tel: +886-2-2516-0500 Fax: +886-2-2516-1501

Hitachi Australia Ltd.

Level 3, 82 Waterloo Road, North Ryde, NSW 2113, Australia

Tel: +61-2-9888-4100 Fax: +61-2-9888-4188 www.hitachi.com.au