

LED / Portable Projector C101i | White

- Contrast Ratio: 1,200:1

- Aspect Ratio: 16:9 (Native), 4:3 (Compatible)

- Throw Ratio: 1625.60 mm@2000 mm

- Lamp Life: 20000 Hour (Normal Mode); 30000 Hour (Economy Mode)

- Resolution: FWVGA (854 x 480)

- Brightness: 150 lm

Ideas in your pocket

Share your ideas wherever you go with Acer Portable LED Projectors. Discuss concepts, show videos on big screens and motivate others while you're on the road -- without needing a computer. With models as slim as 1" (24.5 mm), the world of self-expression now fits in your pocket.





Easy to bring

Your presentations can now fit in a pocket -- or your palm.¹ Be PC-free: Project your content directly from a plugged-in USB drive, or SD™ Card, or even a smartphone.¹,² Show your ideas in HD quality by connecting via HDMI® and MHL® ports¹ to HD source devices. Project wirelessly with the Acer eDisplay Pro® app.



| General | | Videa | |
|-----------------------------|-------------------------------|-----------------------------|--|
| Manufacturer Part Number | MR.JQ411.001 | Video Signal Standard | HDTV |
| EAN | 4713883409636 | Audio | |
| Technical Information | | Number of Speakers | 1 |
| Projection Method | Front | Output Power | 1 W |
| Platform Supported | PC | Speaker Output Mode | Mono |
| Compatibility | Windows PC | Interfaces/Ports | |
| Projection Lens | | HDMI | Yes |
| Lens Type | Manual Focus | USB | Yes |
| Maximum Lens Aperture | F/2,4 | Audio Line Out | Yes |
| Maximum Focal Length | 9.10 mm | Power Description | contracts for the contract contract of the con |
| Minimum Diagonal Image Size | 508 mm | Power Supply | 100 V AC~240 V AC |
| Maximum Diagonal Image Size | 2540 mm | Input Voltage | • 120 V AC • 230 V AC |
| Minimum Projection Distance | 600 mm | Operating Power Consumption | 12 W |
| Maximum Projection Distance | 3 m | Physical Characteristics | |
| Lamp | | Colour | White |
| Lamp Type | LED | Height | 26 mm |
| Number of Lamps | 1 | Width | 118 mm |
| Normal Mode Lamp Life | 20000 Hour | Depth | 121 mm |
| Economy Mode Lamp Life | 30000 Hour | Weight (Approximate) | 265 g |
| lmage | | Fan Noise | 33 dB Approximate Economy Mode |
| Maximum Vertical Sync | 60 Hz | Temperature | 5°C to 35°C |
| Minimum Vertical Sync | 50 Hz | Humidity | 20% to 80% Relative Humidity |
| Maximum Horizontal Sync | 32,20 kHz | Miscellaneous | |
| Color Supported | 16.7 Million Colours (24-bit) | Package Contents | C101i DLP Projector AC to DC Power Adapter Quick Start Guide Tripod |
| Maximum Resolution | 1920 x 1080 | | |
| Native Resolution | 854 x 480 | | |
| Native Aspect Ratio | 16:09 | | |
| Compatible Aspect Ratio | 4:03 | | |
| Contrast Ratio | 1,200:1 | | |
| | | | |



150 lm

75 lm

Throw Ratio

Standard Mode Brightness

Low Mode Brightness

1.4 (1625.60 mm@2000 mm)