

PLC-WXU10

WXGA Ultraportable Multimedia Projector



ULTRA-COMPACT, FULLY PORTABLE DESIGN

Not much larger than a laptop PC, the PLC-WXU10 weighs less than 7.7 pounds and delivers high picture quality in a versatile, go-anywhere system.

TRUE WIDE XGA RESOLUTION

Compatible with wide screen laptops for a true wide screen WXGA (16:10) presentation.

INSTALLATION FEATURES

May be ceiling or inverse mounted for enhanced usage / installation versatility.

F1.75-1.9 ZOOM LENS with 1.2X OPTICAL ZOOM

Which produces a crisp, bright 2,000 ANSI Lumen and the optical zoom helps highlight important program segments.

VERSATILE INPUTS

The PLC-WXU10 offers excellent flexibility via inputs DVI-D and a D-Sub 15. It even has component video inputs. Also there is a D-Sub 15 terminal for monitor output for greater programming flexibility.

AUTO INPUT SEARCH

Searches, finds and displays incoming source signal automatically.

SOFT CARRYING CASE

Zip and go case great for carrying and storing the projector.



PRESENTATION TECHNOLOGIES

21605 Plummer Street
Chatsworth, CA 91311
Ph: 888-337-1215 (toll-free)
Fax 818.717.2719
www.sanyolcd.com

TENTATIVE Specifications

Resolution	WXGA (1280 x 800)
Brightness	2000 ANSI Lumens
Uniformity	80%
LCD Panel System	0.56" TFT Poly x 3
Number of Pixels	3,072,000 (1280 x 800 x 3)
Image Size (diagonal)	40" – 300"
Aspect Ratio	16:10
Throw Distance	4.2' – 39.1'
Zoom/Focus	Manual
Zoom Ratio	1:1.2
Up/Down Ratio	100:-1
Digital Keystone Correction	Vertical: +/- 16°
Projection System	Polarized Beam Splitter optical system
Projection Lens	F1.75-1.9 / f0.74"-0.87"
Lens Throw Ratio	1.52-1.82:1
Projection Lamp	210W NSH
Scanning Frequency	H Sync: 15-80kHz, V Sync: 50-85Hz
Dot Clock	110MHz
Color System	PAL/PAL-M/PAL-N/SECAM/NTSC/NTSC4.43
Computer Compatibility	SXGA, WXGA, XGA, SVGA, VGA
Sound Output	One-piece, 2.0-watt Mono
Voltage	100-240V AC (auto Voltage) ; 50/60 Hz
BTU Rating	955
dB Rating	TBA
Power Consumption	280W
Dimensions (WxHxD)	11.7" x 3.9" x 9.2" (including Adjustable Feet)
Net Weight	7.7 lbs.
User Maintenance	Clean air filters, replace lamp assembly
PC Input Terminals	D-Sub15 x 1 • DVI-D x 1
Video Input Terminals	• Component Video (RCA x 3) • Composite Video (RCA x 1) • S-Video (Mini-DIN 4-pin) • R & L audio (RCA x 2)
Output Terminals	D-Sub15 x 1
Included Accessories	• I/R Remote Control • 2 AAA Batteries • Owner's Manual • VGA Cable • Lens Cap • AC Power Supply Cord • Soft Carrying Case
Optional Accessories	• POA-CA-COMPVGA – VGA/Component Video Cable • POA-MCSRL02 – RS232C Cable • 610 336 0362 – Replacement Lamp
Service Port	Mini DIN 6-pin
Warranty	Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

