



## PDG-DSU20E

- Resolution: 800 x 600 (SVGA)
- Brightness: 2,000 ANSI lumens
- Contrast ratio: 2,000 : 1
- Light weight of only 2.5 kg
- Adjustable up to 300-inch diagonal screen size
- Vertical keystone correction +/-15°
- HDTV compatible
- Built-in speakers
- 3 years warranty

## PDG-DSU20E

TECHNICAL DETAILS	PDG-DSU20E
Category	Business & Education
Panel	1 x 0,55" DMD Chip (4 : 3)
Projection Lamp	180 W UHP (LMP-118)
Brightness ANSI lumens	2,000
Lamp Life	3,000 h (eco mode)/2,500 h (normal mode)
Fan Noise	32 dB (eco mode)/35 dB (normal mode)
Standard Lens	F = 2.51–2.69/f = 21.9–24.2 mm*
Throw Distance Ratio	1.92–2.1 : 1*
Throw Distance	1.2–12.0 m*
Contrast Ratio	2,000 : 1
Resolution in Pixels	800 x 600 (SVGA)
Image size min–max (diagonal)	30"–300"
Uniformity	80%
Bandwidth/Frequency	25–135 MHz, horizontal 31~79 kHz, vertical 50~85 Hz
Colour Systems	PAL/SECAM/NTSC/NTSC4.43/PAL-M/N
Connections	Input 1: D-Sub15 (RGB) Input 2: RCA (Composite) Input 3: Mini DIN 4-pin (S-Video) Audio: 3.5 mm stereo jack Control Input Jack: USB type B (Mouse Control)
Audio Function	2 W Mono
Keystone Correction	Vertical +/-15°
Up/Down-Ratio	13.3 : -1 (Fixed U/D Ratio)
HDTV Compatibility	720p/1,035i/1,080i (HDTV-compatible)
Computer Compatibility	SXGA/XGA/SVGA/VGA
Zoom/Focus	1,1 x/manual focussing
Power Consumption/Voltage	200 W (eco mode)/230 W (normal mode)/100–240 V
Warranty	3 years
Dimensions (W x H x D)	271 x 95 x 223 mm
Weight	2.5 kg
Standard Accessories	Remote control, batteries, user manual, power cable, D-Sub15 cable
Optional Accessories	Component/D-Sub15 cable (POA-CA-COMPVGA), ceiling mounts: 15 cm (POA-CM01), 40–70 cm (POA-CM02), 70–110 cm (POA-CM03)
Lenses	Standard Lens

\* You can use the distance calculator at [www.sanyo.de](http://www.sanyo.de) to determine exact image sizes and distances



Technical specifications are subject to change without notice. Status 09/2007