Dell Advanced Projector- 7760

Dell Large Displays for Conference Rooms and Classrooms



Lamp-free. High Brightness.

Powerful, high-brightness projector with lamp-free laser technology built for presentations in mid-size to large rooms.

- Lose the lightbulb: Lamp-free lasers provide continuous operation at a bright 5,400 lumens, for beautiful projection even in less-than-ideal light.
- **Easy connectivity:** Take advantage of multiple wireless connectivity solutions. You can centralize presentations through LAN display and project from any compatible laptops and tablets.
- **Plan on a long life**: With no lamps to replace and 20,000 hours of laser life, you'll need little IT or facilities maintenance.

Luminous laser projection from every angle.

- **Project instantly:** Lamp-free laser technology eliminates lag-time with instant on and off, minus warm up and cool down time. Laser projection also provides a brilliant gamut of rich, true colors (100% SRGB and 100% Rec.709).
- **The best and brightest:** With 5,400 lumens, you'll get clear, powerful projections, even in settings with suboptimal light.
- Any angle, anytime: The 7760 is engineered to project perfectly from any angle—even on its side or upside down. It can run 24/7, and has a low power consumption, making it perfect for use even in demanding environments such as digital signage.

Simple, seamless connectivity.

- Stay connected, but ditch the cables: Use the concealed compartment for your own 3rd party wireless display solution, or the rear mounting for the Dell Wireless Module-WR517 for cable-free presentation.
- **Command the room from any device:** LAN Display lets you present from anywhere on your network, and from nearly any compatible device, including laptops, smart phones and tablets.
- **Created for collaboration:** The Dell 7760 makes working together easy, with built-in conference controls, you can present from up to four different devices simultaneously.
- **Turn it on, turn it up:** Two high-quality, integrated speakers provide excellent, Dell Class-C onboard sound, so your presentation is ready-equipped with powerful audio.

Reliable performance, dependable support.

- Your projector comes with a 2-year Advanced Exchange, extendable warranty that also covers your laser.
- Remote, centralized management through LAN control/Creston makes it easy for you to manage your projectors and assist users, without having to visit each room

Dell Advanced Projector-7760

Projector with optional ceiling pole mount kit

Technology

Lamp Type

Projection System



Ports and Connectors



- A. RJ45
- B. USB Type A 5V DC / 1.8 A Output
- C. HDMI
- D. HDMI
- E. VGA-In
- F. Audio input (blue)
- G. Microphone (pink)
- H. Audio output (green)
- I. VGA-Out
- J. RS232 (9-pin D-Sub)
- K. 12V DC/ 200 mA max relay output

What's in the box:

• 1x Dell 7760 Projector

• 1x Power cord

- 1x VGA cable (1.8m / 5.9ft)
- 1x Remote control c/w batteries
- User's Guide & Documentation (CD)

| | The ease block |
|-----------------------------|---|
| Native Resolution | FullHD 1080p (1920 x 1080) |
| Screen Size | 26.6" ~ 302" |
| Contrast Ratio | 1,800:1 (native) 100,000:1 (High Contrast Mode) |
| Brightness (Max) | 5,400 ANSI lumens |
| Colors | 1.07b |
| Lens | |
| F-Stop | F/2.3 ~ 3.15 |
| Focal Length Lens Offset | 1.3m – 8.2m 105% ~ 130% |
| | 100/6 0 100/6 |
| Throw Ratio | 1.2 (wide) ~ 2.13 (tele) |
| Lamp Hours | Up to 20,000 hours (Normal Mode) |
| Keystone | Manual Vertical (± 30°) / Manual Horizontal (± 30°) |
| A | Four corner adjustment |
| Audio | 2 x 10W RMS (Stereo) speaker |
| 3D Capable | Yes |
| Design Features Features | LAN Dianlay, 4 in 1 career charing 760° energies |
| Features | LAN Display, 4-in-1 screen sharing, 360° operation, 24/7 operation, 100% SRGB, 100% Rec. 709 |
| Tilt | Front tilt adjustment wheel (0° ~ 3.6°) |
| Security | Kensington lock slot (security lock not included) Password protection |
| Interfaces | |
| | 3x HDMI (1.4a) 1x Audio-In (3.5mm) 1x Audio-Out (3.5mm) 1x D-Sub VGA-In 1x D-Sub VGA-Out 1x Microphone (3.5mm) 2x Powered USB Type A (5V / 1.8 A Output) 1x RS232 (9-pin D-Sub) 1x RJ45 1x 12V DC / 200 mA max. relay output for automatic screen |
| Dimensions & Weight | |
| Width | 405mm/ 15.94 inches |
| Height | 129mm/ 5.08 inches |
| Depth | 387mm/ 15.24 inches |
| Weight | 24.47 lbs (11.1 kg) |
| Power | |
| Power Supply | Universal AC 100-240 V 50-60 Hz with PFC |
| Power Consumption | Normal Mode: 455W <u>+</u> 10% @ 110 Vac |
| | Eco-Mode: 280W ± 10% @ 110 Vac Standby Mode: ≤0.5 W Network Mode: ≤3W |
| Additional Details | · |
| Mounting Options | Front/Rear/Ceiling/Tabletop |
| Noise | 36 dB(A) Typical (Normal Mode) 32 dB(A) Typical (Eco-Mode) |
| | 32 UB(A) Typical (ECO-MOUE) |

Single Chip DLP Dual LVDS

Mercury-free Laser Diode

Warranty:

• 2-year Advanced Exchange warranty, including laser

