

# TOSHIBA

Leading Innovation >>>

| x100



> **MOBILE  
PRESENTATION**

> **HIGH CLASS  
DESIGN**

> **EASY  
TO USE**

- 1.8 kg
- 2,200 ANSI-lumens
- Contrast 600:1



# ProSelecta

View :: Compare :: Select - [www.ProSelecta.com](http://www.ProSelecta.com)

Display	0.63" LCD Chip
Resolution	XGA 1,024 x 768
Brightness	2,200 ANSI-lumens
Colour reproduction	16.7 mio. colours
Contrast	600:1
Projection format	4:3 switchable to 16:9
Lamp	180 W (TLPLW21)
Max. lamp life	up to max. 2,000 hours/ up to max. 3,000 hours in ECO mode
Lens	F = 1.70 - 1.87 / f = 19.2 - 23.1 mm, manual focus and zoom
Zoom	1.2 x
Frequency (hor./vert.)	15 - 106 kHz / 50 - 85 Hz
Projection	front, rear and ceiling
Digital keystone correction	Full auto vertical +/- 45°
Picture size (diagonal)	0,7 - 7,7 m
Projection offset	71 %
Input signals	NTSC / PAL / SECAM, 480i, 480p, 576i, 576p, 720p, 1,080i, 1,080p, VGA, SVGA, XGA, SXGA (compr.)
Inputs	2 x RGB (D-sub 15), audio, video (1 x RCA), S-video
Outputs	1 x RGB switchable in/out, audio
Serial interface	RS-232C (D-sub 9pin)
Power supply	AC 100 - 240 V, 50/60 Hz
Loudspeaker	1 W mono
Dimensions (W x H x D)	268 x 70 x 189 mm
Weight	1.8 kg
Operation noise	ECO Mode 28 dB / normal 32 dB
Specials	auto keystone correction, instant shut down, user logo capture, password, auto setup
Accessories	remote control with batteries, softcase, owners manual (CD-ROM), RGB- and power-cable
Options	ceiling mount, spare lamp, camera c001, RJ45 control adapter
Menu guidance	22 languages: English, French, German, Italian, Spanish, Portuguese, Russian, Swedish, Turkish, Polish, Chinese (simple/traditional), Indonesian, Danish, Czech, Hungari- an, Dutch, Finnish, Norwegian, Greek, Rumanian, Arabic

