

3,000 LUMENS ● XGA ● ULTRAPORTABLE PROJECTOR

PLC-XR301

ULTRAPORTABLE PROJECTOR



3LCD



Built-in Network



Closed Caption

ULTRA-COMPACT, FULLY PORTABLE XGA DESIGN

Not much larger than a laptop PC, the PLC-XR301 weighs less than 5.5 pounds and delivers true XGA picture quality in a versatile, go anywhere system. Also the PLC-XR301 may be mounted ceiling or inverse for enhanced versatility.

COMPLETE EASY AUTO SET UP FUNCTION, SMART AUTO INPUT SEARCH AND AUTO VERTICAL KEYSTONE CORRECTION

PLC-XR301 provides "Auto Set Up Function" that corrects keystone shaped distortion by searching for an input signal and detecting projector incline, therefore reducing set up time. PLC-XR301 automatically compensates for keystone picture distortion. Auto Keystone Correction, Auto Input Search and Auto PC Adjustment make it a easy to use smart projector.

WIRED LAN (RJ-45) FOR NETWORK PROJECTOR CONTROL

This model is equipped with Wired LAN (RJ-45) that allows you to manage and control the projector via Network. It is possible to check the operating time of lamp and manage the warning notification by email. Power ON/OFF and switching of the input signal can be controlled.

DUAL D-SUB15 INPUTS

The PLC-XR301 offers excellent flexibility via a pair of D-Sub15 RGB input terminals. Using an optional adapter cable, it can even accept component video signals. One of the D-Sub15 terminals can even be switched between input and monitor output for greater programming flexibility.

BLACK BOARD / COLOR BOARD MODE

The PLC-XR301 is compatible with four variously colored (red, blue, green, and yellow) projection surfaces via 'Color Board Mode' without a screen.

CLOSED CAPTION

PLC-XR301 is Closed Caption compatible.

| | | |
|--------------------------------|---|---|
| Resolution | XGA (1024 x 768) | |
| Brightness (typical) | 3,000 Lm | |
| Contrast Ratio (Full on / off) | 500:1 | |
| Image Size | 40"-300" | |
| Aspect Ratio | 4:3 | |
| Projection Lamp | 220W | |
| Scanning Frequency | H:15-100kHz, V:50-100Hz | |
| Fan Noise | 29 dBA (Eco) | |
| Voltage | 100-240V AC (auto voltage) ; 50/60 Hz | |
| Power Consumption | 212 W (Eco) | |
| Input signal compatibility | UXGA/ WXGA/ SXGA+/ SXGA/ XGA/ SVGA/ VGA/ MAC | |
| Color System | NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N | |
| Projection Lens (inch) | F 2.00- 2.15 f=0.72" - 0.87" | |
| Throw Ratio | 1.43 - 1.72 : 1 | |
| Throw Distance (feet) | 4.3' - 38.7' | |
| Zoom / Focus | Manual | |
| Up / Down Ratio | 4.3 :1 | |
| Digital Keystone Correction | V +/- 30° MAX | |
| Digital Zoom | 16x - 1/4x | |
| Speaker Output | 1W | |
| Weight (lbs) | 5.5 lbs | |
| Dimensions (inch) W,H,D | 13.1 x 3.4 x 9.7" | |
| Replacement Lamp | 610 345 2456 | |
| Replacement Remote | 645 099 3213 | |
| Lamp Life * (hours) | 4000h (Eco) | |
| Input | PC/Video | D-sub 15 x1 (RGB, Monitor out) D-sub 15 x1 (RGB, Component, S-Video) RCA x1 (Composite) |
| | Audio | Stereo mini jack x 1 |
| Output | PC/Video | D-sub 15 x1 (Monitor out) |
| | Audio | Stereo mini jack x 1 |
| Other Feature | RJ-45 (LAN), Dsub 9pin (RS232C) | |
| Included Accessories | Power cord x 1 VGA cable x 1 Quick reference guide Owner's manual x 1(CD-ROM) Lens Cap x 1 Remote control x 1 (AAA Battery x 2) CD-ROM read me note CD-ROM (PJ-Net Manager application software) PIN code Label Lamp replacement label UL cable card Warranty card | |
| Warranty | Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty | |

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

* Lamp life may vary due to room conditions, usage, and maintenance. The replacement time is a general estimate. The brightness of a lamp usually decreases over time and use.



Back Panel

PRESENTATION TECHNOLOGIES
21605 Plummer Street
Chatsworth, CA 91311
Ph: 888-337-1215 (toll-free)
Fax: 818-717-2719
www.sanyoprojectors.com