

PLC-WXE45

WXGA Ultra Short Focus Projector



PROJECTION FROM 40 INCH AWAY, WITH THE SHORT FOCAL LENGTH LENS

The PLC-WXE 45 can project a full 80-inch image from a distance of only 34 inch. Teachers can project images onto the blackboard right from their desk. This means they can use large images even in relatively small rooms.

WXGA , FITS A VARIETY OF APPLICATION SITUATIONS

Offering a wide XGA full 1366 x 800 (16:10) resolution, the PLC-WXE45 makes it possible to project HD images. This projector is equally comfortable with exquisite HD images from cable/satellite or DVD sources as it is delivering a PC-based presentation in the class room. Compatible with wide screen laptops for a true wide screen WXGA (16:10) presentation

NETWORKING CAPABILITY

The PLC-WXE45 is equipped with SANYO's exclusive PJ Network Interface for wired networking. A common feature among SANYO's extensive line of commercial projectors. Networking allows the monitoring of projector functions and operation from a long distance via a web browser. Emails can be sent automatically to report operating status.

BLACKBOARD, COLORBOARD MODE

In classrooms and other places where there is no screen available, images can be projected onto the blackboard and color board. This enables quick response when making lesson changes or calling a quick meeting.

SPACE SERVING DESIGN

The use of a short-throw lens makes it possible to move the projector from the center of the classroom or meeting room, to a spot closer to the screen. This frees up more room space, and cuts down on the possibility of viewers blocking the image with their shadows.

EASY ON/OFF FUNCTION

The power turns on as soon as you connect the power cord. No need to press any buttons on the remote control or projector. You can disconnect the power cord as soon as the power is turned off.

COMPLETE SECURITY FUNCTIONS

WXE45 cannot be operated without remote control. It can minimize the risk of theft to keep the remote control securely. The PIN code lock guards from an unauthorized user. Anti theft alarm function sounds loudly to prevent theft, when a vibration is detected

CLOSED CAPTION

"Closed captioning provides the audio portion of a television signal as printed words on the projected screen - helpful for deaf and hard of hearing individuals



PRESENTATION TECHNOLOGIES

SANYO

21605 Plummer Street
 Chatsworth, CA 91311
 Ph: 888-337-1215 (toll-free)
 Fax 818.717.2719
www.sanyoprojectors.com

Specifications

| | | | |
|--------------------------------|--|----|--|
| Resolution | WXGA(1,366 x 800) | | |
| Brightness (typical) | 2000 | | |
| Uniformity | 80% | | |
| Panel System | 0.59" TFT Polyx3 | | |
| Number of Pixels | 1,024,000 | | |
| Contrast Ratio (Full on / off) | 500:1 | | |
| Image Size | 50"-110" | | |
| Aspect Ratio | 16:10 | | |
| Projection Lamp (s) | 200W UHP | | |
| Scanning Frequency | H:15-100kHz, V:50-100Hz | | |
| Dot Clock | 140MHz | | |
| Fan Noise | 31dBA | | |
| Voltage | 100-240V | | |
| BTU Rating | 682 | | |
| Power Consumption | 200W | | |
| Input signal compatibility | UXGA/WXGA/SXGA+/SXGA/XGA/SVGA/VGA/MAC, 1080i/50, 1080i/60, 1035i, 720p, 480p, 480i, 575p, 575i | | |
| Color System | NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N | | |
| Projection Lens (inch) | F 1.80 f=0.26" | | |
| Throw Ratio | 0.80 : 1 | | |
| Throw Distance (feet) | 1.7' - 3.9' | | |
| Zoom / Focus | Fix/Manual | | |
| Up / Down Ratio | N/A | | |
| Digital Keystone Correction | V +/- 20° | | |
| Digital Zoom | 16x - 1/4x | | |
| RS-232 Control Carry and / or | Yes | | |
| Speaker Output | 1W | | |
| Weight (lbs.) | 7.5 | | |
| Dimensions (inch) W,H,D | 12.6"x5.7"x11.8" | | |
| Replacement Lamp | 610 332 3855 | | |
| Replacement Remote | 645 093 7231 | | |
| Included Accessories | Owner's manual (CD-ROM) PIN code Label Computer cable (Dsub15-Dsub15) Remote control AA Battery x 2 CD ROM (Application software for Network) | | |
| Optional Accessories | POA-CA-COMPVGA-Component Video Cable POA-MCSRL-Serial control cable POA-CA-SCART - VGA conversion cable | | |
| PC or Video | D-SUB 15-pin | x1 | RGB Component input (Option :with convert cable) |
| PC | D-SUB 15-pin | x1 | RGB Monitor out (common terminal) |
| Video | Mini Din 4 Pin | x1 | S-Video |
| | RCA | x1 | Composite |
| Audio | RCA | x2 | Audio out (variable) |
| | Stereo Mini Jack | x1 | Audio in (Video) |
| | Stereo Mini Jack | x1 | Audio in (PC) |
| Service Port | Mini DIN 8-pin | x1 | (Not use for mouse control) |
| Lan Port | RJ45 | x1 | |
| Warranty | | | 3 years parts and labor; 90 days original lamp; Quick Repair Program under warranty |

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

Rear Back Panel

