



Full 1080p laser projector with high brightness, a full suite of displays ports, and long life ideally suite for meeting room installation venues

**Features**

- Full 1080p (1,920 x 1,080) resolution perfect for HD multimedia presentations and movies
- Solid-state laser phosphor light source for reliable projection and performance
- DLP® DarkChip3™ and BrilliantColor™ technologies for optimal black levels and vibrant colorful images
- Environmentally friendly lamp-less design with an operating time up to 20,000 hours
- 4,500 ANSI lumens with a dynamic 20,000:1 contrast ratio for an amazing image quality
- Manual zoom and focus for easy adjustment and positioning flexibility
- Vertical lens shift and 1.5x zoom ratio for greater installation convenience and flexibility
- 4 segment RGBY color wheel for improved and vivid color reproduction
- Project 3D content from DLP® Link™, and BluRay HDMI 1.4b for realistic life-like images
- Built-in 10W audio speaker with multiple audio-in and audio-out ports
- 360° operation and projection design for set up in all angles
- Portrait mode projection allows the projector to be easily setup and installed in a 90° installation
- Airtight sealed engine and filter-less design for improved performance against fighting dust and fibers
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSDP and Telnet
- Choice of 8 pre-set display scenario modes to get the most suitable display image
- Quick on/off for immediate power on or shutdown
- Anti-theft security features include: Kensington® security slot, security bar, and password protected keypad lock

**Photos**



Specifications				
Display Type	Single Chip 0.65" DLP Technology by TI			
Brightness	4,500 ANSI Lumens			
Native Resolution	1080p (1920 x 1080), 16:9 format			
Contrast Ratio	20,000:1			
Laser Life/Type	20,000 + hours (Laser Phosphor Light Engine)			
Throw Ratio	1.39 - 2.09:1			
Image Size (Diagonal)	25.9" - 324.9"			
Projection Distance	1.2m - 10m (3.9ft – 32.8ft)			
Projection Lens	F#2.42 - 2.97, f=20.7 - 31.05mm			
Zoom Ratio	1.5x			
Aspect Ratio	16:9			
Offset	145%/122.5%			
Keystone Correction	Vertical ±30°			
Horizontal Frequency	15, 31 - 91.4kHz			
Vertical Frequency	24 - 30Hz, 47 - 120Hz			
3D Compatibility	Yes (DLP® Link™, HDMI 1.4 (Blu-Ray 3D))			
Speaker	10W (Mono)			
Lens Shift	Yes (Vertical)			
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac			
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)			
I/O Connection Ports	HDMI v.1.4 (x3)	Audio-In	3.5mm Mini-Jack	
	Composite Video		RCA (L/R)	
	VGA	VGA-In	Audio-Out (3.5mm Mini-Jack)	Mic-In (3.5mm Mini Jack)
		VGA-Out		
	Control	RJ45 (LAN)	Power (5V/1.5A USB Type A)	Mini USB (Service Only)
RS-232c				
Projection Method	Table Top, Ceiling Mount (Front or Rear)			
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock			
Dimensions (WxDxH)	15.5" x 13.3" x 4.9" (395 x 338 x 126mm)			
Weight	Estimated 7kg (15.4lbs)			
Available Colors	White			
Noise Level	35dB/29dB (Normal/Eco. Mode)			
Power Supply	AC 100-240V, 50/60Hz			
Power Consumption	330W (Normal Mode), 260W (Eco. Mode), <0.5W (Standby Mode), <2W (LAN Standby Mode)			
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Documentation Kit			
UPC Code (Projector)	813097024220			

©2017 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximated. Errors and omissions accepted. Specifications are subject to change without prior notice.

