

# Vivitek DU4381Z-ST

High performance WUXGA short-throw projector with a brilliant image HDBaseT™, MHL Compatibility and a full suite of displays ports



## Features

- DLP® DarkChip3™ and BrilliantColor™ technologies for optimal black levels and vibrant colorful images.
- Providing vivid and excellent true color performance cover 91% Rec.709 color gamut and 6% red ratio above.
- Solid state laser phosphor light source for reliable projection and performance
- Environmentally friendly lamp-less design that is mercury-free and energy efficient
- Almost maintenance-free with up to 20,000 hours of operating time
- 6,100 lumens\* with a dynamic 20,000:1 contrast ratio for an amazing image quality
- Delivers up to a 122" image from a distance close to the projection surface
- Short throw projection allows presenter to stand in front of the screen without blocking image, casting shadows and eye glare
- Manual zoom and focus for easy adjustment and positioning flexibility
- Distorted and trapezoid image issues are easily corrected with keystone, and 4-corner adjustment
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- HDBaseT™ interface with support for distribution of HD video and digital audio content over standard CAT5e/6 LAN cable
- Full suite of display connectivity inputs and outputs including: HDMI v1.4b (x2), MHL/HDMI 1.4b, Composite Video, VGA-In, Audio-In RCA (L/R), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), 3D Sync-Out, USB Type A Power (5V/1.5A), RJ45, HDBaseT™, RS232, USB (Service)
- 10W of total stereo audio power (5W x 2) with multiple audio-in and audio-out ports
- 3D sync port for compatibility with IR (infrared) 3D passive synchronization protocol
- 360° operation and projection design for set up in all angles
- Portrait mode projection allows the projector to be easily setup and installed in a 90° installation
- Airtight sealed engine and filter-less design for improved performance against fighting dust and fibers
- Choose from 8 pre-set display modes to get the most suitable display image
- Network ready for integration and system administration via RJ45
- Crestron® RoomView™ integration for network monitoring and management
- Anti-theft security features include: Kensington® security slot, and security bar

## Specifications

Display Type	Single Chip 0.67" DLP Technology by TI
Brightness	6,100 Lumens*
Native Resolution	WUXGA (1920x1200)
Maximum Resolution	WUXGA (1920x1200)@60Hz
Contrast Ratio	20,000:1
Laser Life/Type	20,000 + hours (Laser Phosphor Light Engine)
Throw Ratio	0.5:1
Image Size (Diagonal)	72" - 122" (Focus area)
	72" - 300" (Workable area for video display)
Projection Distance	0.76 - 1.35m (2.5ft - 4.4ft)
Projection Lens	F/2.8 , f=7.46mm
Zoom Ratio	Fixed
Aspect Ratio	16:10
Offset	121%/110.5%
Keystone Correction	Vertical: ±30 steps, Horizontal ±30 steps
Horizontal Frequency	15, 31 - 102kHz
Vertical Frequency	24 - 30Hz, 47 - 120Hz
3D Compatibility	Yes (DLP® Link™, HDMI 1.4 (Blu-Ray 3D))
Speaker	5W (x2)
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
I/O Connection Ports	HDMI v1.4 (x2), MHL/HDMI 1.4, Composite Video, VGA-In, Audio-In RCA (L/R), Audio-In (Mini-Jack), MIC-Out (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), 3D Sync-Out, USB Type A Power (5V/1.5A), RJ45 (LAN), HDBaseT™, RS232, USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (WxDxH)	W/Feet:360 x 440 x 186.3mm (14.2" x 17.8" x 7.3")
	W/O Feet:360 x 440 x 171.3mm (14.2" x 17.8" x 6.74")
Weight	10.5kg (23.1lbs)
Available Colors	White (DU4381Z-ST-WH)
Noise Level	38dB/33dB (Normal/Eco. Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	530W (Normal Mode), 380W (Eco.Mode), <0.5W (Standby Mode), <2W (LAN Standby Mode)
Standard Accessories	AC Power Cord, Remote Control, Documentation Kit
Optional Accessories	N/A

\*Note: Brightness specifications are in compliance with ISO 21118 standards

©2022 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.



## Photos

