



The ultimate home cinema experience

Toshiba presents the **S20 Projector**

Whether it's an all-action blockbuster movie, the big match or latest gaming challenge, nothing beats the sheer thrill of big screen entertainment in the comfort of your own home. Quick and easy to setup, the ultra-portable S20 features simple 'plug and project' functionality so that you can be up and running in less than a minute. The S20's high brightness of 1,400 ANSI lumens defies unfavourable lighting conditions allowing afternoon sports broadcasts to be viewed in near flawless quality.



TOSHIBA

S20 Projector



Superior connectivity

The S20's flexibility is guaranteed by a variety of connections including two RGB and two video inputs (RCA, S-Video), an RGB output and USB and Mini DIN8 interfaces, enabling the projector to process signals from DVD players, video recorders and HD (High Definition) TV tuners as well as from media servers, PCs/Notebooks or digicams. In addition, separate audio connections enable external sound systems to be incorporated for the ultimate home cinema experience. All the S20's functions can be operated from the comfort of your sofa using the convenient remote control supplied.

The ideal solution for home cinema

- Quick and easy to setup
- Superior DLP™ Technology at an affordable price
- Excellent image quality
- Brilliant 1,400 ANSI lumens
- High contrast ratio of 2000:1
- SVGA (800x600) resolution
- Easily switch from 4:3 to 16:9 format
- ECO mode reduces the noise of the fan and extends lamp life
- Accepts PC, DVD, HDTV, gaming console inputs
- Lamp life of 3,000 hours

Model	TDP-S20
Part number	TDP-S20B
Technique	0.7" DMD panel x 1
Resolution	SVGA 800x600
Brightness	1400lm
Lamp	165 W high pressure mercury lamp
Lens	F = 2.0-2.2 / f = 18.2-21.84
Zoom	Manual zoom
Picture size (diagonal)	33-300" diagonal
Projection distance	100 inches/3.3m
Digital keystone correction	Vertical +/- 15°
Contrast	2000:1
Video compatibility	PAL, NTSC, SECAM HDTV (576i/576p/720p/1080i, at 50hz) DVD, game console
Input terminal	2x D-sub 15 terminal, 1x D-sub 15 terminal (common with RGB input), 1x S terminal, 1x RCA terminal, 1x Stereo mini jack, 2x RCA x 2 (L/R)
Outputs terminal	1x D-sub 15 terminal 1x Stereo mini jack (variable audio out)
Other terminal	RS232C (mini DIN8 pin) For service use only
Input signal	NTSC, PAL, SECAM 480i, 480p, 576i, 576p, 1080i, 720p VGA, SVGA (true) / XGA, SXGA, UXGA (compressed)
Serial interface	RS-232C
Integrated loudspeaker	1.0 W, monoaural speaker
Replacement lamp	TLPLV4
Fan noise	36/33dB
Dimensions (w x h x d)	285 x 98 x 254mm
Weight	3.0kg
Remote control	Standard remote
Extras	ECO-mode, auto off
Warranty	2 years parts and labour, 90 days lamp warranty 90 days new product replacement warranty
Accessories	CD-ROM, RGB, audio, AV, power and USB cables, batteries, instructions, softcase
Options	Additional one year warranty, ceiling brackets, screens, PDA & Notebooks, remote control with laser and mouse function